

MC-Estrifan Color Protect Pro

Reference number of the Declaration of Performance: C11822

1. Unique ID code of the product type	MC-Estrifan Color Protect Pro
2. Application(s)	EN 1504-2 Surface protection product coating Protection against ingress (1.3) Physical resistance (5.1)
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	-
5. System of AVCP	System 2+ (for uses in buildings and civil engineering works)
6. Harmonised standard	EN 1504-2: 2004
7. Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754

8. Declared performances


Essential characteristic	Performance	AVCP	harmonised technical specification
Wear resistance	< 3000 mg	System 2+	EN 1504-2: 2004
CO ₂ permeability	Sd > 50 m		
Water vapour permeability	class I		
Capillary water absorption	< 0.1 kg/m ² · h ^{0.5}		
Impact strength	class I: ≥ 4 Nm		
Tear-off test to determine adhesive strength	≥ 1.5 (1.0) N/mm ² The value in brackets is the lowest accepted value of any reading		
Fire behaviour	E _{fl}		
Hazardous substances	EN 1504-2, pt. 5.3		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of Research & Development and Quality

Bottrop, 13.10.2023
(place and date of issue)



The image shows a blue ink signature over a circular stamp. The stamp contains the text 'LEISTUNGSERKLÄRUNG' at the top, 'CE' in the center, and 'DECLARATION OF PERFORMANCE' at the bottom. The 'MC' logo is also visible on the right side of the stamp.

(signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.