

MC-Injekt 1264 TF

Reference number of the Declaration of Performance: IN 5203000

1. Unique ID code of the product type	MC-Injekt 1264 TF
2. Application(s)	Concrete injection for force transmitting filling of cracks, voids and interstices (F), U (F1) W (1) (1) (5/35) (1)
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
5. System of AVCP	System 2+ (for uses in buildings and civil engineering works)
6. Harmonised standard	EN 1504-5: 2004
7. Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754

8. Declared performances


Essential characteristic	Performance	AVCP	harmonised technical specification
Glass transition temperature	> 40 °C	System 2+	EN 1504-5: 2004
Injectability with dry medium	class 1 (0.1 mm)		
Injectability with non-dry medium	class 1 (0.1 mm)		
Durability: Sensitivity to wet/dry cycling	passed		
Adhesion through adhesive tensile strength	> 3 N/mm ²		
Hazardous substances	Accordance with 5.4		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of Research & Development and Quality

Bottrop, 13.10.2023
(place and date of issue)


 (signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.