

Declaration of Performance



Oxal PGP WTA

Reference number of the Declaration of Performance: IN0076421

| | |
|---------------------------------------|--|
| 1. Unique ID code of the product type | Oxal PGP WTA |
| 2. Application(s) | WTA-Restoration render according to WTA restoration render system Part 1: Cladding joint sealants (suitable for use in cold climates) |
| 3. Manufacturer | MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany |
| 4. Authorized representative | MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany |
| 5. System of AVCP | System 4 |
| 6. Harmonised standard | DIN EN 988-1: 2010 |
| 7. Notified body | - |

8. Declared performances


| Essential characteristic | Performance | AVCP | harmonised technical specification |
|---|--|----------|------------------------------------|
| Water absorption | > 1.0 kg/m ² after 24h | System 4 | DIN EN 998-1: 2010 |
| Water vapour permeability | $\mu \leq 18$ | | |
| Water penetration after water absorption test | ≥ 5 mm | | |
| Thermal conductivity | ≤ 0.82 W/(mK) for P=50 % ≤ 0.89 W/(mK) for P=90 % (tabular value acc. EN 1745) | | |
| Fire behaviour | A1 | | |

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of Research & Development and Quality

Bottrop, 13.10.2023
(place and date of issue)



(signature)



Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.