

## Oxal VP III HS

Reference number of the Declaration of Performance: IN0076515

1. Unique ID code of the product type	Oxal VP III HS
2. Application(s)	Concrete injection for force transmitting filling of cracks, voids and interstices (F) U (F1) W (2) (1) (8/35) (1)
3. Manufacturer	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
4. Authorized representative	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 46238 Bottrop / Germany
5. System of AVCP	System 4
6. Harmonised standard	DIN EN 988-2: 2017
7. Notified body	-

8. Declared performances


Essential characteristic	Performance	AVCP	harmonised technical specification
Mixing ratio	Cement: 54 % Lime: 0 % Aggregates/Fillers: 46 %	System 4	DIN EN 998-2: 2017
Durability (frost resistance)	Evaluation dependent on the determinations at the intended production site of the mortar.		
Bond strength	Characteristic initial shear strength (shear strength): 0.30 N/mm <sup>2</sup> (tabular value)		
Water absorption	≤ 0.40 kg/(m <sup>2</sup> x min <sup>0,5</sup> ) (tabular value)		
Water vapour permeability	15/35 (tabular value)		
Fire behaviour	A1		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen  
Head of Research & Development and Quality

Bottrop, 13.10.2023  
(place and date of issue)



(signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.