

Page 1/12

# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

undertaking				
· 1.1 Product identifier				
· Trade name	Colusal SP - Komponente B			
<ul> <li>Article number:</li> <li>1.2 Relevant identified uses of the substance or mixture</li> </ul>	2889			
and uses advised against Application of the substance				
/ the mixture	Epoxy coating Hardening agent/ Curing agent			
• 1.3 Details of the supplier of • Manufacturer/Supplier:	<i>the safety data sheet</i> MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de			
	MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533			
<ul> <li>Informing department:</li> <li>1.4 Emergency telephone</li> </ul>	msds@mc-bauchemie.de			
number:	Tel.: +49 / (0)700 24112112 (MCR) Tel.: +1 872 5888271 (MCR)			
SECTION 2: Hazards ide	entification			
• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008				
Acute Tox. 4 H302 Harm	ful if swallowed.			
Skin Corr. 1B H314 Cause	es severe skin burns and eye damage.			

*Eye Dam.* 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### · 2.2 Label elements

· Labelling according to

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





Page 2/12

## **Safety data sheet** according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

### Trade name Colusal SP - Komponente B

		(Contd. of page 1)
Signal word	Danger	
Hazard-determining		
components of labelling:	Benzyl alcohol	
, 5	polymer amine	terminated
	Isophorone dia	
	Tetraethylenep	
Hazard statements	H302 Harmful i	
		evere skin burns and eye damage.
		se an allergic skin reaction.
		o aquatic life with long lasting effects.
Precautionary statements	P260	Do not breathe dusts or mists.
recould only clatemente		353 IF ON SKIN (or hair): Take off immediately all
	1 000 1 001 1	contaminated clothing. Rinse skin with water [or
		shower].
	P305+P351+P	338 IF IN EYES: Rinse cautiously with water for
	1 000 1 001 1	several minutes. Remove contact lenses, if
		present and easy to do. Continue rinsing.
	P310	Immediately call a POISON CENTER/doctor.
	P321	Specific treatment (see on this label).
	P362+P364	Take off contaminated clothing and wash it
	1 302 11 304	before reuse.
Additional information:	FUH401 To av	oid risks to human health and the environment,
Additional information.		y with the instructions for use.
2.3 Other hazards	comp	
Results of PBT and vPvB as	coccmont	
PBT:	Not applicable.	
rbi. vpvR·	Not applicable.	

· vPvB:

ſ

Not applicable.

# SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description:

Binding agent with colouring agents.
Mixture consisting of the following components.

Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	30-60%
polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	10-30%
Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	<i>≥</i> 10-<25%
Tetraethylenepentamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	<i>≥</i> 5-<10%
	Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319 polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317 Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 Tetraethylenepentamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox.

(Contd. on page 3)



Page 3/12

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

#### Trade name Colusal SP - Komponente B

	(0	Contd. of page 2)
CAS: 69-72-7	salicylic acid	≥1-<1.5%
EINECS: 200-712-3	Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302	-
• Additional information	For the wording of the listed hazard phrases refer to se	ection 16.

### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures			
General information	Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.		
· After inhalation	Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.		
· After skin contact	In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.		
· After eye contact	Rinse opened eye for several minutes under running water. Call a doctor immediately		
· After swallowing	Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.		
<ul> <li>4.2 Most important symptom and effects, both acute and</li> </ul>	IS		
delayed	Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.		

### SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
   5.3 Advice for firefighters
- · Protective equipment:
- Put on breathing apparatus.

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and	
emergency procedures · 6.2 Environmental	Wear protective equipment. Keep unprotected persons away.
precautions: · 6.3 Methods and material for	Prevent material from reaching sewage system, holes and cellars.
	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.
	Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation.

(Contd. on page 4)

<sup>-</sup> GB



Page 4/12

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

(Contd. of page 3)

### Trade name Colusal SP - Komponente B

# 6.4 Reference to other sections

See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling	Open and handle containers with care. Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required. are required. Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or		
	damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins. Open and handle containers with care.		
<ul> <li>Information about protection against explosions and fires:</li> </ul>	Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.		
<ul> <li>7.2 Conditions for safe storag</li> <li>Storage</li> </ul>	· 7.2 Conditions for safe storage, including any incompatibilities		
Requirements to be met by storerooms and containers:	No special requirements.		
storage conditions:	Protect from heat and direct sunlight.		

· Storage class

# SECTION 8: Exposure controls/personal protection

8A

- · 8.1 Control parameters
- Components with critical values that require

*monitoring at the workplace:* The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

	· DNELs		
ſ	CAS: 100-51-6 Benzyl alcohol		
ſ	Oral	DNEL	4 mg/kg bw/Tag (ArL)
			20 mg/kg bw/Tag (Ark)
	Dermal	DNEL	8 mg/kg bw/day (ArL)
			40 mg/kg bw/day (Ark)
			(Contd. on page 5)

\_\_\_\_ GB



Page 5/12

# **Safety data sheet** according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

### Trade name Colusal SP - Komponente B

Inhalat		(Contd. of page
	tive DNEL 22 mg/m <sup>3</sup>	
	110 mg/m	
CAS:	2855-13-2 Isophoron	
Oral	DNEL 0.526 mg	/kg bw/Tag (ArL)
Inhalat	tive DNEL 20.1 mg/r	n³ (ArL)
PNEC	S	
	100-51-6 Benzyl alco	
PNEC	0.527 mg/l (Marine v	vater sediment)
	0.1 mg/l (Mew)	
	1 mg/l (Fresh water	sediment)
PNEC	0.456 mg/kg dwt (Bo	od)
	5.27 mg/kg dwt (Fre	sh water sediment)
CAS:	2855-13-2 Isophoror	ne diamine
PNEC	0.006 mg/l (Mew)	
	0.06 mg/l (Freshwat	er)
PNEC	0.578 mg/kg dwt (Se	ediment)
	5.784 mg/kg dwt (Fr	esh water sediment)
	nic measures	Keep away from food, drink and animal feed.
Breath	nc measures	Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work. Avoid contact with eyes and skin. If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respirator protection must be worn: Use combination filter A1-P2 (brown white) in rooms that cannot be ventilated. If oxygen deficiency expected, use self-contained breathing apparatus. Observ
Hand		Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work. Avoid contact with eyes and skin. If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respirato protection must be worn: Use combination filter A1-P2 (brow white) in rooms that cannot be ventilated. If oxygen deficiency



Page 6/12

# **Safety data sheet** according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

### Trade name Colusal SP - Komponente B

	(Contd. of page 5) materials cannot be calculated in advance and must therefore be checked before use. Nitrile rubber
	Recommended material thickness: ≥ 0.4 mm
Demotration time of stores	Recommended material inickness. 20.4 mm
Penetration time of glove	
material	The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.
	The following applies to all other gloves:
	The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.
	Nitrile rubber
	Material thickness: > 0.40 mm
	Penetration time: > 480 min
	Butyl rubber:
	Material thickness: $\geq 0.5$ mm
	Penetration time: $\geq$ 480 min
<ul> <li>Eye/face protection</li> </ul>	Tight-fitting safety goggles.
	Safety goggles.
<ul> <li>Body protection:</li> </ul>	Protective clothing
	Suitable protective clothing should be worn when working with
	epoxy resins. In addition to normal work clothing (long trousers,
	long-sleeved shirt or T-shirt), disposable overalls, aprons,
	overshoes, sleeve protectors etc. may be necessary depending on
	the activity. Uncovered areas of skin should be avoided as far as
	possible, even in hot weather. If the work involves kneeling, the
	lower leg area should be protected by protective trousers.

## **SECTION 9: Physical and chemical properties**

• 9.1 Information on basic physical and che	emical properties	
General Information		
· Colour:	Yellow	
· Smell:	Amine-like	
<ul> <li>Melting point/freezing point:</li> </ul>	Not determined	
Boiling point or initial boiling point and		
boiling range	205 °C	
· Lower and upper explosion limit		
Lower:	1.3 Vol %	
· Upper:	13 Vol %	
Flash point:	101 °C	
Auto-ignition temperature:	380 °C	
· pH	Not determined.	
Viscosity:		
· Kinematic viscosity	Not determined.	
· dynamic:	Not determined.	
· Solubility		
· Water:	Not miscible or difficult to mix	
		(Contd. on pag

(Contd. on page 7)

GB



Page 7/12

# **Safety data sheet** according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

#### Trade name Colusal SP - Komponente B

	(Contd.	of page
Steam pressure at 20 °C:	0.1 hPa	
Density and/or relative density		
Density at 20 °C	1.04 g/cm³	
9.2 Other information		
Appearance:		
Form:	Fluid	
Important information on protection of hea	alth	
and environment, and on safety.		
Self-inflammability:	Product is not selfigniting.	
Explosive properties:	Product is not explosive.	
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

### SECTION 10: Stability and reactivity

<ul> <li>10.1 Reactivity</li> <li>10.2 Chemical stability</li> <li>Thermal decomposition /</li> </ul>	No further relevant information available.
conditions to be avoided:	No decomposition if used according to specifications.
<ul> <li>10.3 Possibility of hazardous</li> </ul>	
reactions	No dangerous reactions known
<ul> <li>10.4 Conditions to avoid</li> </ul>	No further relevant information available.
<ul> <li>10.5 Incompatible materials:</li> </ul>	No further relevant information available.
10.6 Hazardous	
decomposition products:	No dangerous decomposition products known
	08

(Contd. on page 8)



Page 8/12

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

#### Trade name Colusal SP - Komponente B

(Contd. of page 7)

Acute tox	7	Harmful if swallowed.
	values that are relevan	nt for classification:
	-51-6 Benzyl alcohol	
Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)
CAS: 285	5-13-2 Isophorone dia	mine
Oral	LD50	1030 mg/kg (ATE)
		1030 mg/kg (rat)
NO	NOAEL	250 mg/kg (rat)
Dermal LD50	1840 mg/kg (rabbit)	
		>2000 mg/kg (rat)
CAS: 69-7	72-7 salicylic acid	
Oral	LD50	891 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Skin corr	osion/irritation (	Causes severe skin burns and eye damage.
		Causes serious eye damage.
	ory or skin	
sensitisat		May cause an allergic skin reaction. Based on available data, the classification criteria are not met.
Carcinog	0 7	Based on available data, the classification criteria are not met.
		Based on available data, the classification criteria are not met.
		Based on available data, the classification criteria are not met.
		Based on available data, the classification criteria are not met.
Aspiratio		Based on available data, the classification criteria are not met.
	mation on other hazai	
Endoorin	e disrupting propertie	6

### **SECTION 12: Ecological information**

· · · · · · · · · · · · · · · · · · ·
---------------------------------------

· Aquatic toxicity:

CAS: 100-51-6 Benzyl alcohol

IC50/72h 700 mg/l (algae)

LC50/96h 460 mg/l (Pimephales promelas)

(Contd. on page 9)

GB



Page 9/12

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

#### Trade name Colusal SP - Komponente B

		(Contd. of page 8)
	10 mg/l (Lepomis m	acrochirus)
CAS: 2855	13-2 Isophorone d	iamine
LC50/96h	110 mg/l (Leucidus	idus)
EC50	1120 mg/l (Pseudor	nonas putida)
EC50/48h	23 mg/l (Daphnia m	agna)
NOEC	1.5 mg/l (Desmodes	- /
	3 mg/l (Daphnia ma	
ErC50/72h	ErC50/72h >50 mg/l (Desmodesmus subspicatus)	
· PBT: · vPvB: · 12.6 Endoc properties	cumulative	No further relevant information available. No further relevant information available. No further relevant information available. <b>3 assessment</b> Not applicable. Not applicable. For information on endocrine disrupting properties see section 11.
· Additional · General no	ecological informa tes:	<i>tion:</i> Do not allow product to reach ground water, water bodies or sewage system. Danger to drinking water if even small quantities leak into soil.

### **SECTION 13: Disposal considerations**

• 13.1 Waste treatment methods

- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings: • Recommendation:

*Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.* 

<i>14.1 UN number or ID number ADR, IMDG, IATA</i>	UN2289
14.2 UN proper shipping name ADR, IMDG, IATA	ISOPHORONEDIAMINE
14.3 Transport hazard class(es)	
ADR Class	8 (C7) Corrosive substances.



Page 10/12

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

#### Trade name Colusal SP - Komponente B

	(Contd. of page S
· Label	8
· IMDG, IATA · Class · Label	8 Corrosive substances. 8
· 14.4 Packing group · ADR, IMDG, IATA	<i>III</i>
• 14.5 Environmental hazards: • Marine pollutant:	no No
<ul> <li>14.6 Special precautions for user</li> <li>Kemler Number:</li> <li>EMS Number:</li> <li>Stowage Category</li> <li>Segregation Code</li> </ul>	Warning: Corrosive substances. 80 F-A,S-B A SG35 Stow "separated from" SGG1-acids
<ul> <li>14.7 Maritime transport in bulk according IMO instruments</li> </ul>	ng to Not applicable.
· Transport/Additional information:	
<ul> <li>ADR</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> <li>Transport category</li> <li>Tunnel restriction code</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 E
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> <li>Remarks:</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml cont.: diaminomenthane, isophoronediamine
UN "Model Regulation":	UN 2289 ISOPHORONEDIAMINE, 8, III

### **SECTION 15: Regulatory information**

 15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture

No further relevant information available.

(Contd. on page 11)

- GB



Page 11/12

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

### Trade name Colusal SP - Komponente B

	(Contd. of page 1
<sup>.</sup> Poisons Act	
Regulated explosives pre-	cursors
None of the ingredients is lis	sted.
· Regulated poisons	
None of the ingredients is lis	sted.
· Reportable explosives pre	ecursors
None of the ingredients is lis	sted.
· Reportable poisons	
None of the ingredients is lis	sted.
<ul> <li>15.2 Chemical safety assessment:</li> </ul>	A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases	<ul> <li>H302 Harmful if swallowed.</li> <li>H312 Harmful in contact with skin.</li> <li>H314 Causes severe skin burns and eye damage.</li> <li>H315 Causes skin irritation.</li> <li>H317 May cause an allergic skin reaction.</li> <li>H318 Causes serious eye damage.</li> <li>H319 Causes serious eye irritation.</li> <li>H322 Harmful if inhaled.</li> <li>H361d Suspected of damaging the unborn child.</li> <li>H411 Toxic to aquatic life with long lasting effects.</li> <li>H412 Harmful to aquatic life with long lasting effects.</li> </ul>
<ul> <li>Department issuing data specification sheet:</li> <li>Abbreviations and acronyms:</li> </ul>	Environment protection department. RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent D50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative
	Acute Tox. 4: Acute toxicity – Category 4 (Contd. on page 12)

(Contd. on page 12)

<sup>-</sup> GB



Page 12/12

# **Safety data sheet** according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 24 (replaces version 23)

Revision: 09.03.2024

### Trade name Colusal SP - Komponente B

	(Contd. of page 1 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
	Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B Repr. 2: Reproductive toxicity – Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aqua
	hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aqua hazard – Category 3
<ul> <li>* Data compared to the previous version altered.</li> </ul>	