

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2024 Version number 27 (replaces version 26) Revision: 24.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name Konudur 250 OM-PL Sommerharz - Komponente B

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture Reaction resin

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer.
STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07 GHS08



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2024 Version number 27 (replaces version 26) Revision: 24.02.2024

Trade name Konudur 250 OM-PL Sommerharz - Komponente B

(Contd. of page 1)

· Signal word

Danger

· Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues

· Hazard statements

H315 Causes skin irritation. H319 Causes serious eve irritation.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated

exposure.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/

sprav.

P280 Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P284 [In case of inadequate ventilation] wear

respiratory protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P342+P311 If experiencing respiratory symptoms: Call a

POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container

tightly closed.

· Additional information: EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before

industrial or professional use.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description: Mixture consisting of the following components.

· Dangerous components:

CAS: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues 50-70%

Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1,

H317; STOT SE 3, H335, EUH204

Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 %

Skin Irrit. 2; H315: $C \ge 5 \%$ Resp. Sens. 1; H334: $C \ge 0.1 \%$ STOT SE 3; H335: $C \ge 5 \%$

(Contd. on page 3)



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2024 Version number 27 (replaces version 26) Revision: 24.02.2024

Trade name Konudur 250 OM-PL Sommerharz - Komponente B

	(Co	ntd. of page 2)
CAS: 28553-12-0	diisononyl phthalate	10-30%
EINECS: 249-079-5	substance with a Community workplace exposure limit	
CAS: 2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	≥1-<1.5%
EINECS: 219-784-2	Eye Dam. 1, H318	
· Additional informat	ion For the wording of the listed hazard phrases refer to sec	tion 16

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information Immediately remove any clothing contaminated with the product.

Take affected persons into the open air.

Seek medical treatment.

After inhalation Supply fresh air and call for doctor for safety reasons.
 After skin contact Instantly wash with water and soap and rinse thoroughly.
 After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately.

· After swallowing Call a doctor immediately.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

• 5.2 Special hazards arising from the substance or

mixture Can be released in case of fire

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be

excluded.

· 5.3 Advice for firefighters

· Protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other

sections See Section 7 for information on safe handling

(Contd. on page 4)



Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2024 Version number 27 (replaces version 26)

Trade name Konudur 250 OM-PL Sommerharz - Komponente B

(Contd. of page 3)

Revision: 24.02.2024

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection

against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Information about storage in

one common storage facility: Not required.

· Further information about

storage conditions: Keep container tightly sealed.

· Storage class 10

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require monitoring at the workplace:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m³

Long-term value: 0.02 mg/m3

Sen; as -NCO

CAS: 28553-12-0 diisononyl phthalate

WEL Long-term value: 5 mg/m³

· DNELs

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Inhalative DNEL 0.05 mg/m³ (ArL)

PNECs

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

PNEC 1 mg/l (Sewage Treatment Plant)

0.1 mg/l (Mew)

1 mg/l (Freshwater)

PNEC 1 mg/kg dwt (Bod)

• Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 5)



Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2024 Version number 27 (replaces version 26) Revision: 24.02.2024

Trade name Konudur 250 OM-PL Sommerharz - Komponente B

(Contd. of page 4)

· 8.2 Exposure controls Appropriate engineering

controls No further data: see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment: Respiratory protection is required at inadequately ventilated

> workplaces and during spray processing. Fresh air masks or combination filters A2-P2 are recommended for short-term work.

· Hand protection Conditionally suitable materials for protective gloves; EN 374-3:

Nitrile rubber - NBR: Thickness ≥ 0.35 mm.

Only suitable for splash protection. Only suitable for short-term exposure. In case of contamination, the protective gloves must be

changed immediately. Nitrile rubber, NBR

· Material of gloves

· Penetration time of glove

material

The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

· Eye/face protection Not required.

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid Colour: Dark brown

· Smell: Weak, characteristic · Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

(CAS: 9016-87-9 boiling range 190

diphenylmethanediisocyanate, isomeres and

homologues)

· Lower and upper explosion limit

<0.1 Vol % (CAS: 28553-12-0 diisononyl · Lower:

> phthalate) 0.2 Vol %

· Upper: 201 °C · Flash point:

· Auto-ignition temperature: 400 (CAS: 9016-87-9

diphenylmethanediisocyanate, isomeres and

homologues)

Not determined. · pH

(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2024 Version number 27 (replaces version 26) Revision: 24.02.2024

Trade name Konudur 250 OM-PL Sommerharz - Komponente B

(Contd. of page 5)

· Viscosity:

· Kinematic viscosity Not determined. · dynamic at 20 °C: 400 mPas

· Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 25 °C: h P a (CAS: 9016-87-9

diphenylmethanediisocyanate, isomeres and

homologues)

· Density and/or relative density

· Density at 20 °C 1.16 g/cm3

· 9.2 Other information

· Appearance:

Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting. Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes · Explosives · Flammable gases

· Aerosols

Void Void Void Void

Void

Void

· Oxidising gases · Gases under pressure · Flammable liquids · Flammable solids · Self-reactive substances and mixtures

· Pyrophoric liquids

Pyrophoric solids

Void Void Void Void

Void

Self-heating substances and mixtures

Substances and mixtures, which emit

flammable gases in contact with water Void Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void Corrosive to metals Void Desensitised explosives Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

Reacts with amines reactions

· 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 7)



Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2024 Version number 27 (replaces version 26) Revision: 24.02.2024

Trade name Konudur 250 OM-PL Sommerharz - Komponente B

(Contd. of page 6)

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

		-			
· LD/LC50 values that are relevant for classification:					
	CAS: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues				
	Oral	LD50	>10000 mg/kg (Rat)		
	Dermal	LD50	>5000 mg/kg (Rab)		
	Inhalative	LC50/4 h	~450 mg/l (Rat)		

CAS: 28553-12-0 diisononyl phthalate
Oral LD50 10000 mg/kg (rat)

CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

 Oral
 LD50
 8030 mg/kg (rat)

 Dermal
 LD50
 4248 mg/kg (rabbit)

Skin corrosion/irritation
 Serious eye damage/irritation
 Causes skin irritation.
 Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

• Carcinogenicity Suspected of causing cancer.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure May cause damage to organs through prolonged or repeated

exposure.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 28553-12-0 diisononyl phthalate

EC50/72h 88 mg/l (algae)

LC50/96h | 102 mg/l (Danio rerio)

(Contd. on page 8)



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2024 Version number 27 (replaces version 26) Revision: 24.02.2024

Trade name Konudur 250 OM-PL Sommerharz - Komponente B

(Contd. of page 7)

5050/40/	(Conta. or page 7)	
EC50/48h	74 mg/l (Daphnia magna)	
NOEC	101 mg/l (Daphnia magna)	
CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane		
LC50/96h	55 mg/l (Cyp)	
EC50/48h	473 mg/l (Daphnia magna)	
ErC50/72h	255 mg/l (Scenedesmus subspicatus)	

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.
12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Waste disposal key number: 55903

Bez.: Harzrückstände, nicht ausgehärtet

Entsorgungshinweise: Sonderabfallverbrennung

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

(Contd. on page 9)



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2024 Version number 27 (replaces version 26) Revision: 24.02.2024

Trade name Konudur 250 OM-PL Sommerharz - Komponente B

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to

IMO instruments Not applicable.

· UN "Model Regulation": Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixtureNo further relevant information available.

· Poisons Act

Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

(Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2024

Version number 27 (replaces version 26)

Trade name Konudur 250 OM-PL Sommerharz - Komponente B

(Contd. of page 9)

Revision: 24.02.2024

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or

repeated exposure.

EUH204 Contains isocyanates. May produce an allergic reaction.

Department issuing data

specification sheet:

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par

route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the

previous version altered.