

Page 1/10

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 33 (replaces version 32)

Revision: 12.04.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier	
· Trade name	Konudur Flexfit - Komponente A
 Article number: 1.2 Relevant identified uses of the substance or mixture 	4305
and uses advised against • Application of the substance	No further relevant information available. e
/ the mixture	Polyurethane lacquer
 1.3 Details of the supplier of Manufacturer/Supplier: 	the safety data sheet MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8
	D-46238 Bottrop Tel.: +49(0)2041-101-0
	Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de
	MC-Bauchemie AG
	Hagackerstr. 10 CH-8953 Dietikon
	Tel.: +44-7400510
	Fax : +44-7400533
 Informing department: 1.4 Emergency telephone 	msds@mc-bauchemie.de
number:	Tel.: +49 / (0)700 24112112 (MCR) Tel.: +1 872 5888271 (MCR)
SECTION 2: Hazards id	ontification
SECTION 2. Hazarus lu	
• 2.1 Classification of the sub	
Classification according to I Skin Sens. 1 H317 May	cause an allergic skin reaction.
•	tes damage to the lung through prolonged or repeated exposure

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

- Labelling according to
- **Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word

Danger

(Contd. on page 2)

GB



Page 2/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 33 (replaces version 32)

Revision: 12.04.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 1) Hazard-determining components of labelling: tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate crystalline silica · Hazard statements H317 May cause an allergic skin reaction. H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation. H412 Harmful to aquatic life with long lasting effects. Do not breathe dust/fume/gas/mist/vapours/spray. · Precautionary statements P260 P273 Avoid release to the environment. P280 Wear protective gloves. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P321 Specific treatment (see on this label). P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

3.2 Mixtures Description:	Resin mixture.	
	Mixture consisting of the following components.	
Dangerous components:		
CAS: 136210-30-5 ELINCS: 429-270-1	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL- aspartate	30-60%
Reg.nr.: 01-0000017556-64- xxxx	Skin Sens. 1, H317; Aquatic Chronic 3, H412	
CAS: 14808-60-7	crystalline silica STOT RE 1, H372	10-30%

SECTION 4: First aid measures

• 4.1 Description	of first aid	measures	
Concernel informer	- 4:		

· General information	Remove solled, soaked clothing immediately.
· After inhalation	Remove person to fresh air, keep warm, allow to rest; if breathing
	is difficult, seek medical attention.
· After skin contact	In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
· After eye contact	Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.
	(Contd. on page 3)

GB



Page 3/10

GB

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 33 (replaces version 32)

Revision: 12.04.2024

Trade name Konudur Flexfit - Komponente A

• After swallowing • 4.2 Most important symptoms	(Contd. of page 2) Do NOT induce vomiting. Rinse mouth with water. Medical attention required.
and effects, both acute and delayed	Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.
 4.3 Indication of any immediate medical attention and special treatment needed 	Therapeutic measures: No information available.
SECTION 5: Firefighting	measures
 5.1 Extinguishing media Suitable extinguishing agents 5.2 Special hazards arising from the substance or 	Use fire fighting measures that suit the environment.
mixture • 5.3 Advice for firefighters	No further relevant information available.
• Protective equipment:	No special measures required.
SECTION 6: Accidental r	elease measures
· 6.1 Personal precautions, protective equipment and	
emergency procedures 6.2 Environmental	Not required.
precautions: 6.3 Methods and material for	No special measures required.
containment and cleaning up:	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 6.4 Reference to other sections 	No dangerous materials are released.
SECTION 7: Handling an	
SECTION 1. Handling and	

• 7.1 Precautions for safe handling	Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application. For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored. At workplaces where isocyanate aerosols and/or vapours can
	occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.
	For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling (Contd. on page 4)



Page 4/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 33 (replaces version 32)

Revision: 12.04.2024

Trade name Konudur Flexfit - Komponente A

	(Contd. of page isocyanates must be observed. Avoid contact with skin and ey and inhalation of vapours. Keep away from food and beverages. Wash hands before brea and at the end of work and apply skin protection ointment. Sto work clothes separately. Remove soiled, soaked clothin immediately.
Information about protection	Infinediately.
against explosions and fires:	Keep ignition sources away - do not smoke. Protect from heat. Do not store near heat sources.
7.2 Conditions for safe	
storage, including any incompatibilities	Keep container dry and tightly closed. Further information on t storage conditions that must be observed for quality assuran reasons can be found in our technical data sheet.
Storage	
Requirements to be met by	
storerooms and containers:	Keep tightly closed in original packaging. Ventilate storage roor well. Carefully close opened containers and store upright prevent any leakage.
	Storage temperature >5°C and <30°C
Information about storage in	
one common storage facility:	May be stored together with hazardous substances of oth classes up to 200 kg.
Further information about	
storage conditions: Storage class	Keep container tightly closed in a well-ventilated place. 6.1C
7.3 Specific end use(s)	No further relevant information available.

SECTION 8: Exposure controls/personal protection

 8.1 Control parameters
 Components with critical values that require monitoring at the workplace

monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs CAS: 136	210-30-	-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate
		4 mg/kg bw/day (ArL)
Inhalative	DNEL	28 mg/m ³ (ArL)
		112 mg/m ³ (Ark)
PNECs		
CAS: 136	210-30-	-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate
PNEC 31	.1 mg/l	(Kla)
		(Contd. on pag



Page 5/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 33 (replaces version 32)

Revision: 12.04.2024

Trade name Konudur Flexfit - Komponente A

	0.000013 mg/l (Mew)	(Contd. of page
	0.00013 mg/l (Mew) 0.00013 mg/l (Freshw	(ator)
PNEC	0.1 mg/kg dwt (Bod)	
	0.02 mg/kg dwt (Marir	
	0.21 mg/kg dwt (Fresl	·
Additi	onal information:	The lists that were valid during the compilation were used as basi
	posure controls	
	priate engineering	
contro		No further data; see section 7.
	al protective and	ures, such as personal protective equipment
	nic measures	Do not smoke, eat or drink while working. Have eye wa equipment ready.
		Do not inhale gases/vapours/aerosols. Avoid contact with eyes a skin.
		Do not store food in the work area. Wash hands before breaks a at the end of work.
Breath	ning equipment:	Respiratory protection required at insufficiently ventilate workplaces and when working with splashes. Fresh air masks combination filters A2-P2 (EN529) are recommended for sho term work.
		If applicable, further recommendations for respiratory protection can be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chror
Hand	protection	bronchitis), handling of the product is not recommended. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min Fluororubber - FKM: thickness ≥0.4mm; breakthrough tin
		≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves.
Materi	al of gloves	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
Penetr	ration time of glove	
materi		Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480mir Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough tin ≥480min.
		Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min.
	ce protection	Wear safety goggles/face protection.
Body	protection:	Wear suitable protective clothing when working. In case of hypersensitivity of the skin, handling of the product is n recommended.

(Contd. on page 6)



Page 6/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 33 (replaces version 32)

Revision: 12.04.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 5)

9.1 Information on basic physical and cher General Information	nicai properties
Colour:	According to product specification
Smell:	Characteristic
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and	
boiling range	185 °C (CAS: 136210-30-5 tetraethyl-N,N (methylenedicyclohexane-4,1-diyl)bis-D aspartate)
Flash point:	100 °C
Auto-ignition temperature:	350 °C (CAS: 152637-10-0 poly(oxy(methyl-1, ethanediyl)))
рН	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
Water: Steam pressure at 20 °C:	Not miscible or difficult to mix 2 hPa (CAS: 152637-10-0 poly(oxy(methyl-1, ethanediyl)))
Density and/or relative density	
Density at 20 °C	1.99 g/cm³
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of hea	
and environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive.
Information with regard to physical haze classes	ard
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void



Page 7/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 33 (replaces version 32)

Revision: 12.04.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 6)
-

SECTION 10: Stability and reactivity

· 10.1 Reactivity

No further relevant information available.

 10.2 Chemical stability Thermal decomposition / 	
conditions to be avoided:	No decomposition if used according to specifications.
• 10.3 Possibility of hazardous	
reactions	No dangerous reactions known
 10.4 Conditions to avoid 	No further relevant information available.
 10.5 Incompatible materials: 	No further relevant information available.
10.6 Hazardous	
decomposition products:	No dangerous decomposition products known

SECTION 11: Toxicological information

 11.1 Information on hazard c Acute toxicity 	lasses as defined in Regulation (EC) No 1272/2008 Based on available data, the classification criteria are not met.
•	
· LD/LC50 values that are relevant for classification:	
CAS: 136210-30-5 tetraethyl-	N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate
Oral LD50 >2000 mg/kg (r	at) (67/548/EWG, Annex V, B.1)
Dermal LD50 >2000 mg/kg (r	at) (67/548/EWG, Annex V, B.3)
Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Respiratory or skin	
sensitisation	May cause an allergic skin reaction.
· Germ cell mutagenicity	Based on available data, the classification criteria are not met.
· Carcinogenicity	Based on available data, the classification criteria are not met.
· Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Causes damage to the lung through prolonged or repeated
	exposure. Route of exposure: Inhalation.
 Aspiration hazard 	Based on available data, the classification criteria are not met.
11.2 Information on other hazards	
· Endocrine disrupting properties	
CAS: 128-37-0 2,6-Di-tert-but	yl-p-cresol List II
	GB

(Contd. on page 8)



Page 8/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 33 (replaces version 32)

Revision: 12.04.2024

Trade name Konudur Flexfit - Komponente A

(Contd. of page 7)

· 12.1 Toxicit	/	
· Aquatic tox	city:	
CAS: 13621	0-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	
LC50/96h 6	66 mg/l (Danio rerio) (OECD 203)	
EC50 3	3110 mg/l (BEL)	
EC50/48h 8		
	0.01 mg/l (Daphnia magna)	
ErC50/72h	113 mg/l (Scenedesmus subspicatus)	
· PBT: · vPvB:	umulative No further relevant information available.	
properties 12.7 Other a	For information on endocrine disrupting properties see section 11 dverse effects cological information:	
· General not		

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings: · Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

[.] 14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	



Page 9/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 33 (replaces version 32)

Revision: 12.04.2024

Trade name Konudur Flexfit - Komponente A

		(Contd. of page 8
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
Class	Void	
· 14.4 Packing group		
ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accord	ing to	
IMO instruments	Not applicable.	
· UN "Model Regulation":	Void	

OFOTION AF D I.	1 - · · · · · · · · · · · · · · · · · ·
SECTION 15: Regula	tory information
<u> </u>	

 15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture Poisons Act 	No further relevant information available.
· Regulated explosives precursors	
None of the ingredients is listed.	
· Regulated poisons	
None of the ingredients is listed.	
· Reportable explosives precursors	
None of the ingredients is listed.	
· Reportable poisons	
None of the ingredients is listed.	
 15.2 Chemical safety assessment: 	A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases	H317 May cause an allergic skin reaction. H372 Causes damage to organs through proto exposure. H412 Harmful to aquatic life with long lasting effe	•
 Department issuing data specification sheet: 	Environment protection department.	(Contd. on page 10)

GB



Page 10/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 33 (replaces version 32)

Revision: 12.04.2024

Trade name Konudur Flexfit - Komponente A

· Abbreviations and acronyms:	(Contd. of page 9) <i>RID:</i> Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH)
	LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Sens. 1: Skin sensitisation – Category 1
* Data compared to the	STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
previous version altered.	GB