

Page 1/10

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 01.03.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

MC-DUR 1101 - Komponente A
1162 No further relevant information available.
Epoxy coating
he safety data sheet MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533
msds@mc-bauchemie.de Tel.: +49 / (0)700 24112112 (MCR) Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



Danger

· Signal word

 Hazard-determining components of labelling:

Polymer Epoxidharz-Addukt Aminpolymer 3,6,9-triazaundecamethylenediamine

(Contd. on page 2)



Page 2/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 01.03.2024

Trade name MC-DUR 1101 - Komponente A

Hazard statements	H318 Causes s	erious eye damage.
	H317 May caus	se an allergic skin reaction.
Precautionary statements	P261	Avoid breathing dust/fume/gas/mist/vapours/ spray.
	P280	Wear protective gloves / eye protection / face protection.
	P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing.
	P310	Immediately call a POISON CENTER/doctor.
	P321	Specific treatment (see on this label).
	P362+P364	Take off contaminated clothing and wash in before reuse.

- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Resin mixture with colouring agents. Mixture consisting of the following components.

· Dangerous components:		
CAS: 260549-92-6	Polymer Epoxidharz-Addukt	30-60%
	Eye Dam. 1, H318	
CAS: 180583-06-6	Aminpolymer	≥1-<10%
	Skin Sens. 1, H317	
CAS: 112-57-2	3,6,9-triazaundecamethylenediamine	<i>≥</i> 0.25-<0.5%
EINECS: 203-986-2	Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	
· Additional informa	tion For the wording of the listed hazard phrases refer to	section 16.

SECTION 4: First aid measures		
· 4.1 Description of first aid measures		
General information	Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.	
· After inhalation	Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.	
· After skin contact	In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.	

· After eye contact Rinse opened eye for several minutes under running water. Call a doctor immediately

(Contd. on page 3)

GB



Page 3/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 30 (replaces version 29)

Printing date 09.03.2024

Revision: 01.03.2024

Trade name MC-DUR 1101 - Komponente A

• After swallowing (Contd. of page 2) Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

 4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

• 5.1 Extinguishing media

- Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture
- · 5.3 Advice for firefighters
- · Protective equipment:
- No special measures required.

No further relevant information available.

SECTION 6: Accidental release measures	
6.1 Personal precautions, protective equipment and	
emergency procedures	Not required.
6.2 Environmental	
precautions:	Prevent material from reaching sewage system, holes and cellars. Dilute with much water.
6.3 Methods and material for	
containment and cleaning up	Absorb with liquid-binding material (sand, diatomite, acid binders universal binders, sawdust).
	Dispose of contaminated material as waste according to item 13.
6.4 Reference to other	
sections	See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

 7.1 Precautions for safe handling

Open and handle containers with care.

Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required. are required.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing

(Contd. on page 4)



Page 4/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 01.03.2024

Trade name MC-DUR 1101 - Komponente A

	(Contd. of pag container. Pour carefully and slowly when repotting. Observe BGBau technical data sheet and practical guide for handling epo resins. Open and handle containers with care.
· Information about protection	
against explosions and fires:	Ensure sufficient air exchange and/or extraction in the work areas. Take precautionary measures to avoid electrosta discharges.
· 7.2 Conditions for safe storage	e, including any incompatibilities
· Storage	
Requirements to be met by	
storerooms and containers: Further information about	No special requirements.
storage conditions:	Protect from heat and direct sunlight.
· Storage class	10
SECTION 8: Exposure co	ontrols/personal protection
Components with critical values that require	
monitoring at the workplace:	The product does not contain any relevant quantities of mater with critical values that have to be monitored at the workplace.

· DNELs	-		
CAS: 1	112-57-2 3,	6,9-triazaundecamethylenediamine	
Oral	DNEL	0.53 mg/kg bw/Tag (ArL)	
Derma	DNEL	0.74 mg/kg bw/day (ArL)	
Inhalat	tive DNEL	6940 mg/m³ (ArL)	
·PNEC	S		
CAS: 1	112-57-2 3,	6,9-triazaundecamethylenediamine	
PNEC	9.73 mg/l	BEL)	
	0.0068 mg	/l (Fresh water)	
	0.0068 mg	/l (Mew)	
PNEC	0.343 mg/	(g dwt (Sediment)	
	-	dwt (Fresh water sediment)	
· Additi	onal inforr	nation: The lists that were valid during the compilation were	used as basis.
· Appro contro			
	al protecti		
	nic measui		
		-	(Contd. on page 5)



Page 5/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 01.03.2024

Trade name MC-DUR 1101 - Komponente A

Breathing equipment:	(Contd. of page 4) If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/ white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.
Hand protection	Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Material of gloves	You can find help with choosing gloves on the website https:// www.bgbau.de/fileadmin/Gisbau/Projekte.pdf For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. Nitrile rubber
Penetration time of glove	Recommended material thickness:≥ 0.4 mm
material	The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours. The following applies to all other gloves: The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to. Nitrile rubber Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min Butyl rubber: Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min
Eye/face protection	Tight-fitting safety goggles. Safety goggles.
Body protection:	Protective clothing Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.
	GB

(Contd. on page 6)



Page 6/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 01.03.2024

Trade name MC-DUR 1101 - Komponente A

(Contd. of page 5)

9.1 Information on basic physical and chei	mical properties
General Information	
Colour:	Transparent
Smell:	Characteristic
Melting point/freezing point:	<0 °C
Boiling point or initial boiling point and	
boiling range	100 °C (CAS: 7732-18-5 water, distille
	conductivity or of similar purity)
Flash point:	151 °C
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	
Water:	Fully miscible
Steam pressure at 20 °C:	23 hPa (CAS: 7732-18-5 water, distille
	conductivity or of similar purity)
Vapour pressure at 50 °C:	<5 hPa
Density and/or relative density	
Density at 20 °C	1.07 g/cm³
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of hea	alth
and environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive.
Information with regard to physical haz	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void

(Contd. on page 7)

GB



Page 7/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 01.03.2024

(Contd. of page 6)

Trade name MC-DUR 1101 - Komponente A

· Corrosive to metals · Desensitised explosives

Void Void

SECTION 10: Stability and reactivity

10.1 Reactivity
 10.2 Chemical stability

No further relevant information available.

No decomposition if used according to specifications.

conditions to be avoided: 10.3 Possibility of hazardous reactions 10.4 Conditions to avoid

Thermal decomposition /

- No dangerous reactions known No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Based on available data, the classification criteria are not met.

· I D/I C50 values that are relevant for classification:

· LD/LC50 values that are relevant for classification:		
CAS: 112-57-2 3,6,9-triazaundecamethylenediamine		
Oral LD50 2140 mg/kg (ra	at)	
Dermal LD50 1260 mg/kg (ra	abbit)	
 Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/irritation Causes serious eye damage. Respiratory or skin 		
sensitisation Germ cell mutagenicity	May cause an allergic skin reaction. Based on available data, the classification criteria are n	ot met
· Carcinogenicity	Based on available data, the classification criteria are n	ot met.
 Reproductive toxicity STOT-single exposure 	Based on available data, the classification criteria are n Based on available data, the classification criteria are n	ot met.
• STOT-repeated exposure Based on available data, the classification criteria are not met. • Aspiration hazard Based on available data, the classification criteria are not met. • 11.2 Information on other hazards		
· Endocrine disrupting properties		
CAS: 541-02-6 2,2,4,4,6,6,8,8	8,10,10-decamethylcyclopentasiloxane	List II
CAS: 556-67-2 octamethylcy	clotetrasiloxane	List II; III

(Contd. on page 8)

GB



Page 8/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 01.03.2024

Trade name MC-DUR 1101 - Komponente A

(Contd. of page 7)

· 12.1 Toxicity	
· Aquatic toxicity:	
CAS: 112-57-2 3,6,9-triaz	aundecamethylenediamine
EC50/72h 2.1 mg/l (algae	
LC50/96h 420 mg/l (Gup)	
EC50/48h 24.1 mg/l (Daphnia magna)	
12.2 Persistence and	
degradability	No further relevant information available.
12.3 Bioaccumulative	
potential	No further relevant information available.
 12.4 Mobility in soil 	No further relevant information available.
12.5 Results of PBT and	vPvB assessment
· PBT:	Not applicable.
· vPvB:	Not applicable.
• 12.6 Endocrine disruptin	g
properties	For information on endocrine disrupting properties see section 11
12.7 Other adverse effec	
· Additional ecological inf	ormation:
· General notes:	Do not allow product to reach ground water, water bodies sewage system.
	Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

 13.1 Waste treatment metho Recommendation 	ds Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
· Uncleaned packagings: · Recommendation:	Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.
 Recommended cleaning agent: 	Water, if necessary with cleaning agent.

SECTION 14: Transport information		
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void	
 14.2 UN proper shipping name ADR, ADN, IMDG, IATA 	Void	
		(Contd. on page 9) GI



Page 9/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 01.03.2024

Trade name MC-DUR 1101 - Komponente A

		(Contd. of page 8
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
[.] Class	Void	
· 14.4 Packing group		
ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accord	ing to	
IMO instruments	Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information	
 15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture Poisons Act 	No further relevant information available.
· Regulated explosives precursors	
None of the ingredients is listed.	
· Regulated poisons	
None of the ingredients is listed.	
· Reportable explosives precurs	sors
None of the ingredients is listed.	
· Reportable poisons	
None of the ingredients is listed.	
 15.2 Chemical safety assessment: 	A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phr	ases
--------------	------

rases	H302 Harmful if swallowed.	
	H312 Harmful in contact with skin.	
	H314 Causes severe skin burns and eye damage.	
	H317 May cause an allergic skin reaction.	
	H318 Causes serious eye damage.	
	H411 Toxic to aquatic life with long lasting effects.	

(Contd. on page 10)

GB



Page 10/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 30 (replaces version 29)

Revision: 01.03.2024

Trade name MC-DUR 1101 - Komponente A

 Department issuing data specification sheet: Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)		(Contd. of page S
specification sheet: Environment protection department. Abbreviations and acronyms: RD: Réglement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International AirTransport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal dose, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic VPW: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquat. hazard – Category 2	· Department issuing data	
Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerou Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Level (UK REACH) DNEL: Derived No-Effect Level (UK REACH) ELD50: Lethal concentration, 50 percent LD50: Lethal cose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquat hazard – Category 2		Environment protection department.
0,0		 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par oute (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquational approximation.
	· * Data compared to the	huzuna outogory z
previous version altered.		