

Page 1/12

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier	
· Trade name	MC-DUR 1101 - Komponente B
 Article number: 1.2 Relevant identified uses of the substance or mixture 	1165
and uses advised against Application of the substance	No further relevant information available.
/ the mixture	Epoxy coating Hardening agent/ Curing agent
• 1.3 Details of the supplier of a	the safety data sheet MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533
 Informing department: 1.4 Emergency telephone 	msds@mc-bauchemie.de
number:	Tel.: +49 / (0)700 24112112 (MCR) Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP

· Hazard pictograms



(Contd. on page 2)

GB



Page 2/12

GB

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

Trade name MC-DUR 1101 - Komponente B

		(Contd. of page 1)	
· Signal word	Warning		
· Hazard-determining			
components of labelling:	epoxide derivates		
		of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]	
		-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)	
		2'-[methylenebis(2,1-phenyleneoxymethylene)]	
	dioxirane		
		(C12-14-alkyloxy)methyl] derivatives	
 Hazard statements 	H315 Causes skin irritation.		
		erious eye irritation.	
	-	e an allergic skin reaction.	
		quatic life with long lasting effects.	
 Precautionary statements 	P261	Avoid breathing dust/fume/gas/mist/vapours/	
	P273	spray. Avoid release to the environment.	
	P273 P280	Wear protective gloves / eye protection / face	
	1200	protection.	
	P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for	
	1 000 1 001 1 0	several minutes. Remove contact lenses, if	
		present and easy to do. Continue rinsing.	
	P333+P313	If skin irritation or rash occurs: Get medical	
		advice/attention.	
	P337+P313	If eye irritation persists: Get medical advice/	
		attention.	
 Additional information: 	EUH205 Conta	ins epoxy constituents. May produce an allergic	
	reactio	n.	
 2.3 Other hazards 			
• Results of PBT and vPvB as			
· PBT:	Not applicable.		
· vPvB:	Not applicable.		

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Binding agent with colouring agents. Mixture consisting of the following components.

· Dangerous componei	nts:	
CAS: 1675-54-3	epoxide derivates	30-60%
EINECS: 216-823-5	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	
CAS: 9003-36-5 EC number: 701-263-0	Reaction mass of 2,2'-[methylenebis(4,1- phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'- [methylenebis(2,1-phenyleneoxymethylene)]dioxirane	
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 68609-97-2 EINECS: 271-846-8	Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	10-30%
	Skin Irrit. 2, H315; Skin Sens. 1, H317, EUH205	
	(Contd	. on page 3)



Page 3/12

GB

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

Trade name MC-DUR 1101 - Komponente B

· Additional information	(Contd. of page 2) For the wording of the listed hazard phrases refer to section 16.		
SECTION 4: First aid measures			
• 4.1 Description of first aid	measures		
· General information	Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.		
· After inhalation	Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.		
· After skin contact	In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.		
· After eye contact	Rinse opened eye for several minutes under running water. Call a doctor immediately		
· After swallowing	Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms		

 4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents Use fire fighting measures that suit the environment.

persist, consult a doctor.

5.2 Special hazards arising from the substance or mixture No 5.3 Advice for firefighters

No further relevant information available.

- Protective equipment:
- No special measures required.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and 	
emergency procedures	Not required.
6.2 Environmental	
precautions:	Prevent material from reaching sewage system, holes and cellars.
6.3 Methods and material for	
containment and cleaning up	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
• 6.4 Reference to other	
sections	See Section 7 for information on safe handling
	See Section 8 for information on personal protection equipment.
	(Contd. on page 4)



Page 4/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

Trade name MC-DUR 1101 - Komponente B

See Section 13 for information on disposal.

(Contd. of page 3)

SECTION 7: Handling and storage

[.] 7.1 Precautions for safe handling	Open and handle containers with care. Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required. are required. Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins. Open and handle containers with care.
 Information about protection against explosions and fires: 	Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
 7.2 Conditions for safe storag Storage Requirements to be met by storerooms and containers: Further information about storage conditions: Storage class 	ne, including any incompatibilities No special requirements. None. 10

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs			
CAS: 686	09-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	
Oral	DNEL	1 mg/kg bw/Tag (ArL)	
Dermal	DNEL	1.7 mg/kg bw/day (ArL)	
Inhalative	DNEL	0.98 mg/m³ (ArL)	
· PNECs			
CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives			
PNEC 0.0	00072 n	ng/l (Mew)	
			(Contd. on page 5)

GB



Page 5/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

Trade name MC-DUR 1101 - Komponente B

0.0072 mg/l (Freshv	(Contd. of page
PNEC 80.12 mg/kg dwt (Bo	
	,
6.677 mg/kg dwt (Se	
	resh water sediment)
Additional information:	The lists that were valid during the compilation were used as bas
· 8.2 Exposure controls	
Appropriate engineering	
controls	No further data; see section 7.
	sures, such as personal protective equipment
General protective and	Kana and from food drink and an incal food
hygienic measures	Keep away from food, drink and animal feed. Remove soiled, soaked clothing immediately.
	Wash hands before breaks and at the end of work.
	Avoid contact with eyes and skin.
Breathing equipment:	If workplace limit values cannot be complied with by ventilati
caunig equipment.	measures or if rooms cannot be technically ventilated, respirate
	protection must be worn: Use combination filter A1-P2 (brow
	white) in rooms that cannot be ventilated. If oxygen deficiency
	expected, use self-contained breathing apparatus. Obser
	wearing time limits according to §9 (3) GefStoffV in conjuncti
	with BGR 190.
Hand protection	Selection of the glove material on consideration of the penetrati
Material of alarras	times, rates of diffusion and the degradation
Material of gloves	You can find help with choosing gloves on the website https
	www.bgbau.de/fileadmin/Gisbau/Projekte.pdf For example, we recommend the Sol-vex 37-900 protective glov
	from Ansell GmbH. The breakthrough time of the protective glov
	can be found under point 8 "Penetration time of the glove materia
	The selection of a suitable glove depends not only on the materia
	but also on other quality features and varies from manufacturer
	manufacturer. As the product
	is a preparation of several substances, the resistance of glo
	materials cannot be calculated in advance and must therefore
	checked before use.
	Nitrile rubber
Departmention time of alare	Recommended material thickness: > 0.4 mm
Penetration time of glove	The breakthrough times of the Sol-vex 37-900 protective glov
material	are around 8 hours.
	The following applies to all other gloves:
	The exact breakthrough time must be obtained from the protect.
	glove manufacturer and adhered to.
	Nitrile rubber
	Material thickness: \geq 0.40 mm
	Penetration time: \geq 480 min
	Butyl rubber:
	Material thickness: $\geq 0.5 \text{ mm}$
	Penetration time: \geq 480 min
	(Contd. on page



Page 6/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

Trade name MC-DUR 1101 - Komponente B

	(Contd. of page 5)
 Eye/face protection 	Tight-fitting safety goggles.
	Safety goggles.
 Body protection: 	Protective clothing
	Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical and chen General Information 	nical properties
· Colour:	Yellow
· Smell:	Characteristic
	Not determined
• Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and	> 200 °C (CAC: 25068 28 6 Brand 2.2 dinhand
boiling range	>200 °C (CAS: 25068-38-6 Propyl -2,2-diphenyl- 4,4'dipropyloxirane polymers and homologues molecular weight < 700)
· Flash point:	140 °C
• Auto-ignition temperature:	184 °C (CAS: 25068-38-6 Propyl -2,2-diphenyl- 4,4'dipropyloxirane polymers and homologues molecular weight < 700)
∙рН	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible or difficult to mix
Steam pressure at 20 °C:	<0.1 hPa (CAS: 25068-38-6 Propyl -2,2-diphenyl-
	4,4'dipropyloxirane polymers and homologues molecular weight < 700)
 Density and/or relative density 	
· Density at 20 °C	1.1 g/cm³
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
 Important information on protection of heat 	lth
and environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
	(Contd. on page 7
	0



Page 7/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

Trade name MC-DUR 1101 - Komponente B

		(Contd. of page
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

 10.1 Reactivity 10.2 Chemical stability Thermal decomposition / 	No further relevant information available.
conditions to be avoided: 10.3 Possibility of hazardous	No decomposition if used according to specifications.
reactions	No dangerous reactions known
 10.4 Conditions to avoid 	No further relevant information available.
 10.5 Incompatible materials: 10.6 Hazardous 	No further relevant information available.
decomposition products:	No dangerous decomposition products known

SECTION 11: Toxicological information

 \cdot 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Based on available data, the classification criteria are not met.

· Acute toxicity

· LD/LC50 values that are relevant for classification:

CAS: 1675-54-3 epoxide derivates

Dermal LD50 23000 mg/kg (rabbit)

(Contd. on page 8)

GB



Page 8/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

Trade name MC-DUR 1101 - Komponente B

and 2-(*	(Contd. of page 7) on mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane {2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'- lenebis(2,1-phenyleneoxymethylene)]dioxirane		
Oral LD50 >2000 mg	>2000 mg/kg (rat)		
Dermal LD50 >2000 mg	>2000 mg/kg (rabbit)		
CAS: 68609-97-2 Oxirar	CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives		
Oral LD50 17100 mg/kg (rat)			
Skin corrosion/irritatior	n Causes skin irritation.		
· Serious eye damage/irr	itation Causes serious eye irritation.		
Respiratory or skin			
sensitisation	May cause an allergic skin reaction.		
· Germ cell mutagenicity	Based on available data, the classification criteria are not met.		
· Carcinogenicity	Based on available data, the classification criteria are not met.		
· Reproductive toxicity	Based on available data, the classification criteria are not met.		
STOT-single exposure	Based on available data, the classification criteria are not met.		
· STOT-repeated exposu			
· Aspiration hazard	Based on available data, the classification criteria are not met.		
11.2 Information on other hazards			
· Endocrine disrupting p	· Endocrine disrupting properties		
None of the ingredients is listed.			

SECTION 12: Ecological information

Aquatic to	kicity:
CAS: 1675-	54-3 epoxide derivates
IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)
	36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2' [methylenebis(2,1-phenyleneoxymethylene)]dioxirane
LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)
CAS: 68609	9-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives
EbC50/72h	843 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>5000 mg/l (Oncorhynchus mykiss)
	1800 mg/l (Lepomis macrochirus)
EC50	>100 mg/l (BEL)
NOFO	500 mg/l (Pseudokirchneriella subcapitata)
NOEC	obo mgn (r seddoki ennenena subcapitata)

- GB



Page 9/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

Trade name MC-DUR 1101 - Komponente B

	(Contd. of page 8)
 12.2 Persistence and 	
degradability	No further relevant information available.
· 12.3 Bioaccumulative	
potential	No further relevant information available.
12.4 Mobility in soil	No further relevant information available.
12.5 Results of PBT and vPvB	3 assessment
PBT:	Not applicable.
vPvB:	Not applicable.
12.6 Endocrine disrupting	
properties	The product does not contain substances with endocrine disrupting properties.
12.7 Other adverse effects	
Additional ecological informa	tion:
General notes:	Do not allow product to reach ground water, water bodies or sewage system.
	Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods
 • Recommendation
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 • Uncleaned packagings:

· Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
ADR, IATA	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)
IMDG	ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (epoxide derivates, MARINE POLLUTANT
[.] 14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous dangerous substances an articles.
Label	9
· IMDG, IATA	
Class	9 Miscellaneous dangerous substances an articles.
	(Contd. on page 1



Page 10/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

Trade name MC-DUR 1101 - Komponente B

Label	(Contd. of page
	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances an
	articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk accordi	ing to
IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100
	ml
Transport category	3
Tunnel restriction code	(-)
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 100
	ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
-	SUBSTANCE, LIQUID, N.O.S. (EPOXIDI
	DERIVATES), 9, III

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

(Contd. on page 11)

[–] GB



Page 11/12

- GB

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

Trade name MC-DUR 1101 - Komponente B

	(Contd. of page 10)
· Regulated poisons	
None of the ingredients is listed	
· Reportable explosives precu	sors
None of the ingredients is listed	
· Reportable poisons	
None of the ingredients is listed	
· Directive 2012/18/EU	
· Qualifying quantity (tonnes)	
for the application of lower-	
tier requirements	200 t
Qualifying quantity (tonnes)	
for the application of upper-	
tier requirements	500 t
 15.2 Chemical safety 	
assessment:	A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases	 H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects. EUH205 Contains epoxy constituents. May produce an allergic reaction.
 Department issuing data specification sheet: Abbreviations and acronyms: 	Environment protection department. RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 (Contd. on page 12)



Page 12/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 26 (replaces version 25)

Revision: 09.03.2024

Trade name MC-DUR 1101 - Komponente B

(Contd. of page 11)

GB

Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

• * Data compared to the previous version altered.