



BE SURE. BUILD SURE.

Page 1/15

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name **MC-DUR 1291 flex - Komponente B**

· Article number: 831

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Epoxy coating
Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· Informing department: msds@mc-bauchemie.de

· 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 2 H373 May cause damage to the liver, the immune system and the gastrointestinal tract through prolonged or repeated exposure.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Page 2/15

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1291 flex - Komponente B

(Contd. of page 1)

· **Hazard pictograms**



GHS05 GHS07 GHS08 GHS09

· **Signal word**

Danger

· **Hazard-determining components of labelling:**

2-Propennitril, Polymer mit 1,3-Butadien, 1-Cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminiert
Isophorone diamine
2-piperazin-1-ylethylamine
2,4,6-tris(dimethylaminomethyl)phenol
2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid
trimethylhexane-1,6-diamine

· **Hazard statements**

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H373 May cause damage to the liver, the immune system and the gastro-intestinal tract through prolonged or repeated exposure.

· **Precautionary statements**

H410 Very toxic to aquatic life with long lasting effects.
P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture consisting of the following components.

(Contd. on page 3)

GB



BE SURE. BUILD SURE.

Page 3/15

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name **MC-DUR 1291 flex - Komponente B**

(Contd. of page 2)

Dangerous components:

CAS: 68683-29-4	2-Propennitril, Polymer mit 1,3-Butadien, 1-Cyano-1-methyl-4-oxo-4-[[2-(1-piperaziny)ethyl]amino]butyl-terminiert Skin Irrit. 2, H315; Skin Sens. 1, H317	30-60%
CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥5-<10%
CAS: 61788-44-1 EINECS: 262-975-0	2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<10%
CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<10%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34	Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<5%
CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	≥3-<5%
CAS: 69-72-7 EINECS: 200-712-3	salicylic acid Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302	≥1-<3%
CAS: 25620-58-0 EINECS: 247-134-8 Reg.nr.: 2119560598-25	trimethylhexane-1,6-diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	≥1-<3%
CAS: 61788-46-3 EINECS: 262-977-1 Reg.nr.: 2119473798-17	Amines, coco alkyl STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302; STOT SE 3, H335	≥2.5-<3%
CAS: 140-31-8 EINECS: 205-411-0 Reg.nr.: 01-2119471486-30	2-piperazin-1-ylethylamine Repr. 2, H361fd; STOT RE 1, H372; Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<2.5%

Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.

After inhalation

Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Page 4/15

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1291 flex - Komponente B

(Contd. of page 3)

- **After skin contact** *In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.*
- **After eye contact** *Rinse opened eye for several minutes under running water.
Call a doctor immediately*
- **After swallowing** *Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.*
- **4.2 Most important symptoms and effects, both acute and delayed** *Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.*

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** *Use fire fighting measures that suit the environment.*
- **5.2 Special hazards arising from the substance or mixture** *No further relevant information available.*
- **5.3 Advice for firefighters**
- **Protective equipment:** *Put on breathing apparatus.*

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Wear protective equipment. Keep unprotected persons away.*
- **6.2 Environmental precautions:** *Prevent material from reaching sewage system, holes and cellars.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.*
- **6.4 Reference to other sections** *See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.*

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *Open and handle containers with care.
Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required.*

(Contd. on page 5)

GB



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1291 flex - Komponente B

(Contd. of page 4)

are required.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins. Open and handle containers with care.

· **Information about protection**

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:**

No special requirements.

· **Further information about storage conditions:**

Protect from heat and direct sunlight.

· **Storage class**

8A

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require**

monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

CAS: 2855-13-2 Isophorone diamine

Oral DNEL 0.526 mg/kg bw/Tag (ArL)

Inhalative DNEL 20.1 mg/m³ (ArL)

CAS: 100-51-6 Benzyl alcohol

Oral DNEL 4 mg/kg bw/Tag (ArL)

20 mg/kg bw/Tag (Ark)

Dermal DNEL 8 mg/kg bw/day (ArL)

40 mg/kg bw/day (Ark)

Inhalative DNEL 22 mg/m³ (ArL)

110 mg/m³ (Ark)

Reaction mass of ethylbenzene and xylene

Oral DNEL 1.6 mg/kg bw/Tag (ArL)

mg/kg bw/Tag (Workers)

Dermal DNEL 180 mg/kg bw/day (ArL)

Inhalative DNEL 211 mg/m³ (ArL)

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1291 flex - Komponente B

(Contd. of page 5)

CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

Inhalative DNEL 0.31 mg/m³ (ArL)

CAS: 140-31-8 2-piperazin-1-ylethylamine

Dermal DNEL 3.33 mg/kg bw/day (ArL)

Inhalative DNEL 10.6 mg/m³ (ArL)

· PNECs

CAS: 2855-13-2 Isophorone diamine

PNEC 0.006 mg/l (Mew)

0.06 mg/l (Freshwater)

PNEC 0.578 mg/kg dwt (Sediment)

5.784 mg/kg dwt (Fresh water sediment)

CAS: 100-51-6 Benzyl alcohol

PNEC 0.527 mg/l (Marine water sediment)

0.1 mg/l (Mew)

1 mg/l (Fresh water sediment)

PNEC 0.456 mg/kg dwt (Bod)

5.27 mg/kg dwt (Fresh water sediment)

CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

PNEC 0.2 mg/l (Sewage Treatment Plant)

0.0084 mg/l (Mew)

0.084 mg/l (Freshwater)

CAS: 140-31-8 2-piperazin-1-ylethylamine

PNEC 250 mg/l (Kla)

0.0058 mg/l (Mew)

0.058 mg/l (Freshwater)

PNEC 1 mg/kg dwt (Bod)

21.5 mg/kg dwt (Sediment)

215 mg/kg dwt (Fresh water sediment)

· CAS No. Designation of material % Type Value Unit

· Additional Occupational Exposure Limit Values for possible hazards during processing:

CAS: 1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

CAS: 100-41-4 Ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm

Long-term value: 441 mg/m³, 100 ppm

Sk

· Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/15

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name **MC-DUR 1291 flex - Komponente B**

(Contd. of page 6)

- **8.2 Exposure controls**
- **Appropriate engineering controls**
No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
*Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.*
- **Breathing equipment:**
If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.
- **Hand protection**
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
*You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material".
The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.
Nitrile rubber
Recommended material thickness: ≥ 0.4 mm*
- **Penetration time of glove material**
*The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.
The following applies to all other gloves:
The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.
Nitrile rubber
Material thickness: ≥ 0.40 mm
Penetration time: ≥ 480 min
Butyl rubber:
Material thickness: ≥ 0.5 mm
Penetration time: ≥ 480 min*
- **Eye/face protection**
*Tight-fitting safety goggles.
Safety goggles.*
- **Body protection:**
*Protective clothing
Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on*

(Contd. on page 8)



BE SURE. BUILD SURE.

Page 8/15

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1291 flex - Komponente B

(Contd. of page 7)

the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:	Yellow
· Smell:	Amine-like
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	205 °C
· Flash point:	101 °C
· Auto-ignition temperature:	435 °C
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	13800 mPas
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C	1 g/cm ³

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void

(Contd. on page 9)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1291 flex - Komponente B

(Contd. of page 8)

· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 2855-13-2 Isophorone diamine

Oral	LD50	1030 mg/kg (ATE) 1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit) >2000 mg/kg (rat)

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

Reaction mass of ethylbenzene and xylene

Oral	LD50	3523-4000 mg/kg (rat)
Dermal	LD50	1100 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (rat)

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1291 flex - Komponente B

(Contd. of page 9)

CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

Oral	LD50	mg/kg (rat)
	NOAEL	15 mg/kg (rat)

CAS: 69-72-7 salicylic acid

Oral	LD50	891 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

CAS: 25620-58-0 trimethylhexane-1,6-diamine

Oral	LD50	910 mg/kg (rat)
------	------	-----------------

CAS: 140-31-8 2-piperazin-1-ylethylamine

Oral	LD50	2000-5000 mg/kg (rat) 500 mg/kg (rabbit)
Dermal	LD50	200-1000 mg/kg (rabbit)

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** May cause damage to the liver, the immune system and the gastro-intestinal tract through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· **Endocrine disrupting properties**

CAS: 61788-44-1	2,4,6-Tris-(1-Phenyl-Ethyl) carboic acid	List II
CAS: 69-72-7	salicylic acid	List II; III

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 2855-13-2 Isophorone diamine

LC50/96h	110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodesmus subspicatus) 3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodesmus subspicatus)

CAS: 100-51-6 Benzyl alcohol

IC50/72h	700 mg/l (algae)
----------	------------------

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1291 flex - Komponente B

(Contd. of page 10)

LC50/96h	460 mg/l (<i>Pimephales promelas</i>) 10 mg/l (<i>Lepomis macrochirus</i>)
Reaction mass of ethylbenzene and xylene	
EC50/72h	2.2 mg/l (<i>Selenastrum capricornutum</i>)
LC50/96h	2.6 mg/l (<i>Oncorhynchus mykiss</i>)
NOEC	16 mg/l (BEL)
CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol	
EC50/72h	84 mg/l (<i>Desmodesmus subspicatus</i>)
LC50/96h	175 mg/l (<i>Cyp</i>) 718 mg/l (<i>Daphnia magna</i>)
NOEC	2 mg/l (BEL) 6.25 mg/l (<i>Desmodesmus subspicatus</i>)
CAS: 25620-58-0 trimethylhexane-1,6-diamine	
LC50/96h	31.5 mg/l (<i>Daphnies</i>)
CAS: 140-31-8 2-piperazin-1-ylethylamine	
EC50/72h	>1000 mg/l (algae)
LC50/96h	2190 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Danger to drinking water if even extremely small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1291 flex - Komponente B

(Contd. of page 11)

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN2289
· 14.2 UN proper shipping name · ADR · IMDG · IATA	ISOPHORONEDIAMINE solution, ENVIRONMENTALLY HAZARDOUS ISOPHORONEDIAMINE solution, MARINE POLLUTANT ISOPHORONEDIAMINE solution
· 14.3 Transport hazard class(es) · ADR · Class · Label	8 (C7) Corrosive substances. 8
· IMDG, IATA · Class · Label	8 Corrosive substances. 8
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	Product contains environmentally hazardous substances: 2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid Yes Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Kehler Number: · EMS Number: · Stowage Category · Segregation Code	Warning: Corrosive substances. 80 F-A, S-B A SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information: · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 E

(Contd. on page 13)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name **MC-DUR 1291 flex - Komponente B**

(Contd. of page 12)

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 2289 ISOPHORONEDIAMINE SOLUTION, 8, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation.
---------------------------	--

(Contd. on page 14)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1291 flex - Komponente B

(Contd. of page 13)

- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

· **Abbreviations and acronyms:**

Environment protection department.

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

(Contd. on page 15)



BE SURE. BUILD SURE.

Page 15/15

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 08.03.2024

Version number 35 (replaces version 34)

Revision: 08.03.2024

Trade name MC-DUR 1291 flex - Komponente B

(Contd. of page 14)

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.

GB