

Page 1/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 32 (replaces version 31) Revision: 10.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name <u>MC-DUR 1322 - Kompo</u>nente A

· Article number: 4072

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Epoxy coating

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

· 1.4 Emergency telephone

number:

msds@mc-bauchemie.de

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP

regulation.

· Hazard pictograms





GHS07 GHS09

· Signal word

Warning

(Contd. on page 2)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 32 (replaces version 31) Revision: 10.03.2024

Trade name MC-DUR 1322 - Komponente A

(Contd. of page 1)

· Hazard-determining

components of labelling: epoxide derivates

Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]

dioxirane

maleic anhydride

· **Hazard statements** H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/

sprav.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical

advice/attention.

P337+P313 If eye irritation persists: Get medical advice/

attention.

· Additional information: EUH205 Contains epoxy constituents. May produce an allergic

reaction.

EUH211 Warning! Hazardous respirable droplets may be formed

when sprayed. Do not breathe spray or mist.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:		
CAS: 1675-54-3 EINECS: 216-823-5	epoxide derivates Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	30-60%
CAS: 14808-60-7	crystalline silica STOT RE 1, H372	10-30%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	≥1-<5%
		(Contd. on page 3)

GB



Page 3/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 32 (replaces version 31) Revision: 10.03.2024

Trade name MC-DUR 1322 - Komponente A

		(Contd. of page 2)
CAS: 68609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	≥1-<5%
EINECS: 271-846-8	Skin Irrit. 2, H315; Skin Sens. 1, H317, EUH205	
CAS: 9003-36-5 EC number: 701-263-0	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	<i>≥</i> 2.5-<5%
CAS: 100-51-6	Benzyl alcohol	<2.5%
	Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	
CAS: 222417-26-7	Polyacrylate	<i>≥</i> 0.025-<0.25%
	Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	
CAS: 108-31-6	maleic anhydride	<0.001%
EINECS: 203-571-6	Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071	
	Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	
· Additional information	For the wording of the listed hazard phrases refer	to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

· After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

• After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

• After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

(Contd. on page 4)



Page 4/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 10.03.2024 Printing date 10.03.2024 Version number 32 (replaces version 31)

Trade name MC-DUR 1322 - Komponente A

(Contd. of page 3)

 5.2 Special hazards arising from the substance or

mixture

No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment:

No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures

Not required.

· 6.2 Environmental

precautions:

Prevent material from reaching sewage system, holes and cellars.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle containers with care.

Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required.

are required.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins. Open and handle containers with care.

· Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: None.

(Contd. on page 5)



Page 5/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 32 (replaces version 31) Revision: 10.03.2024

Trade name MC-DUR 1322 - Komponente A

(Contd. of page 4)

· Storage class

10

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 108-31-6 maleic anhydride

WEL Short-term value: 3 mg/m³

Long-term value: 1 mg/m3

Sen

· DNELs

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives

Oral DNEL 1 mg/kg bw/Tag (ArL)
Dermal DNEL 1.7 mg/kg bw/day (ArL)
Inhalative DNEL 0.98 mg/m³ (ArL)

CAS: 100-51-6 Benzyl alcohol

Oral DNEL 4 mg/kg bw/Tag (ArL)

20 mg/kg bw/Tag (Ark)

Dermal DNEL 8 mg/kg bw/day (ArL)

40 mg/kg bw/day (Ark)

Inhalative DNEL 22 mg/m³ (ArL)

110 mg/m³ (Ark)

PNECs

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives

PNEC 0.00072 mg/l (Mew)

0.0072 mg/l (Freshwater)

PNEC 80.12 mg/kg dwt (Bod)

6.677 mg/kg dwt (Sediment)

66.77 mg/kg dwt (Fresh water sediment)

CAS: 100-51-6 Benzyl alcohol

PNEC | 0.527 mg/l (Marine water sediment)

0.1 mg/l (Mew)

1 mg/l (Fresh water sediment)

PNEC 0.456 mg/kg dwt (Bod)

5.27 mg/kg dwt (Fresh water sediment)

Additional information:

The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering

controls

No further data; see section 7.

(Contd. on page 6)



Page 6/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 10.03.2024 Printing date 10.03.2024 Version number 32 (replaces version 31)

Trade name MC-DUR 1322 - Komponente A

(Contd. of page 5)

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

· Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/ white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

· Hand protection Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

· Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be

checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

· Penetration time of glove material

· Eye/face protection

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

Safety goggles. · Body protection: Protective clothing

> Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.



Page 7/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 32 (replaces version 31) Revision: 10.03.2024

Trade name MC-DUR 1322 - Komponente A

(Contd. of page 6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Grey

Smell: CharacteristicMelting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range >200 °C (CAS: 1675-54-3 bis[4-(2,3-

epoxypropoxy)phenyl]propane)

· Flash point: >249 °C · Auto-ignition temperature: 184 °C

pH Not applicable.

Not determined.

· Viscosity:

Kinematic viscositydynamic:Not determined.Not determined.

Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: 0.1 hPa

· Density and/or relative density

· Density at 20 °C 1.69 g/cm³

· 9.2 Other information

· Appearance:

Fluid

· Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.
Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

Void · Explosives Void · Flammable gases · Aerosols Void Void Oxidising gases · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Void

Self-heating substances and mixtures Substances and mixtures, which emit

flammable gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void

(Contd. on page 8)



Page 8/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 32 (replaces version 31) Revision: 10.03.2024

Trade name MC-DUR 1322 - Komponente A

(Contd. of page 7)

· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute tox	ricity B	ased on available data, the classification criteria are not met.
LD/LC50	values that are relevant	t for classification:
CAS: 167	5-54-3 epoxide derivate	es
Dermal	LD50	23000 mg/kg (rabbit)
CAS: 134	63-67-7 titanium dioxid	e
Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)
CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives		
Oral	LD50	17100 mg/kg (rat)
	and 2-({2-[4-(ox	of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirai iran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2 ,1-phenyleneoxymethylene)]dioxirane
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
CAS: 100	-51-6 Benzyl alcohol	
Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)
		(Contd. on page

(Contd. on page 9)



Page 9/13

List II

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 32 (replaces version 31) Revision: 10.03.2024 Printing date 10.03.2024

Trade name MC-DUR 1322 - Komponente A

(Contd. of page 8)

CAS: 108-31-6 maleic anhydride

Oral LD50 1090 mg/kg (rat) Dermal LD50 2620 mg/kg (rat)

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

CAS: 128-37-0 2,6-Di-tert-butyl-p-cresol

SECTION 12: Ecological information

· 12.1 Toxici	•	
	54-3 epoxide derivates	
IC50	>42.6 mg/l (Bak)	
LC50/96h	2 mg/l (Oncorhynchus mykiss)	
EC50/48h	1.8 mg/l (Daphnia magna)	
ErC50/72h	11 mg/l (Selenastrum capricornutum)	
CAS: 68609	9-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	
EbC50/72h	843 mg/l (Pseudokirchneriella subcapitata)	
LC50/96h	>5000 mg/l (Oncorhynchus mykiss)	
	1800 mg/l (Lepomis macrochirus)	
EC50	>100 mg/l (BEL)	
NOEC	500 mg/l (Pseudokirchneriella subcapitata)	
CAS: 9003-	36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	
LC50/96h	>100 mg/l (Daphnia magna)	
EC50/96h	>100 mg/l (Leucidus idus)	
CAS: 100-5	1-6 Benzyl alcohol	
IC50/72h	700 mg/l (algae)	
LC50/96h	460 mg/l (Pimephales promelas)	
	10 mg/l (Lepomis macrochirus)	

(Contd. on page 10)



Page 10/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 32 (replaces version 31) Revision: 10.03.2024

Trade name MC-DUR 1322 - Komponente A

(Contd. of page 9)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR, IATA IMDG	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (epoxide derivate Oxirane, mono[(C12-14-alkyloxy)methy derivatives) ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (epoxide derivate
14.3 Transport hazard class(es)	Oxirane, mono[(C12-14-alkyloxy)methy derivatives), MARINE POLLUTANT
ADR	
Class	9 (M6) Miscellaneous dangerous substances an articles.
Label	9

--- page .



Page 11/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.03.2024 Version number 32 (replaces version 31) Revision: 10.03.2024

Trade name MC-DUR 1322 - Komponente A

	(Contd. of page 1
IMDG, IATA Class Label	9 Miscellaneous dangerous substances an articles. 9
14.4 Packing group ADR, IMDG, IATA	
14.5 Environmental hazards: Marine pollutant: Special marking (ADR): Special marking (IATA):	Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances ar
Kemler Number: EMS Number: Stowage Category	articles. 90 F-A,S-F A
14.7 Maritime transport in bulk accordi IMO instruments	i ng to Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
Transport category Tunnel restriction code	3 (-)
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (EPOXID DERIVATES, OXIRANE, MONO[(C12-14 ALKYLOXY)METHYL] DERIVATIVES), 9, III



Page 12/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 10.03.2024 Printing date 10.03.2024 Version number 32 (replaces version 31)

Trade name MC-DUR 1322 - Komponente A

(Contd. of page 11)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- · Qualifying quantity (tonnes)

for the application of lowertier requirements

200 t

· Qualifying quantity (tonnes)

for the application of upper-

tier requirements

500 t

· 15.2 Chemical safety

A Chemical Safety Assessment has not been carried out. assessment:

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated

exposure.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410

Toxic to aquatic life with long lasting effects. H411

EUH071 Corrosive to the respiratory tract.

(Contd. on page 13)



Page 13/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 10.03.2024 Printing date 10.03.2024 Version number 32 (replaces version 31)

Trade name MC-DUR 1322 - Komponente A

(Contd. of page 12)

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· Department issuing data

specification sheet: Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity - Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard -

Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

* * Data compared to the previous version altered.