



BE SURE. BUILD SURE.

Page 1/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR 1390 VK - Komponente B**

Article number: 2673

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Epoxy impregnation
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07

Signal word

Danger

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 1)

- **Hazard-determining components of labelling:** polymer amine terminated
2-methylpentane-1,5-diamine
salicylic acid
3,6,9-triazaundecamethylenediamine
Tetraethylenepentamine
- **Hazard statements** H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
- **Precautionary statements** P260 Do not breathe dusts or mists.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Binding agent with colouring agents.
Mixture consisting of the following components.

| · Dangerous components: | | |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| EC number: 949-140-2 | polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317 | 30-60% |
| CAS: 100-51-6 | Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319 | 30-60% |
| CAS: 15520-10-2 EINECS: 239-556-6 | 2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335 | ≥10-<20% |
| CAS: 69-72-7 EINECS: 200-712-3 | salicylic acid Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302 | ≥1-<1.5% |
| CAS: 112-57-2 EINECS: 203-986-2 | 3,6,9-triazaundecamethylenediamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1B, H317 | ≥0.25-<1% |

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

Trade name **MC-DUR 1390 VK - Komponente B**

| | | |
|---------------------------------------------------------------------------------------------------|------------------------------------------------------|-----------------------------------|
| CAS: 90640-66-7 | Tetraethylenepentamine | (Contd. of page 2) ≥0.25-<0.5% |
| EINECS: 292-587-7 | Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute | |
| Reg.nr.: 01-2119487290-37 | Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317 | |
| · Additional information For the wording of the listed hazard phrases refer to section 16. | | |

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation.

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 3)

· **6.4 Reference to other sections**

See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Open and handle containers with care.
Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins. Open and handle containers with care.

· **Information about protection against explosions and fires:**

Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:**

No special requirements.

· **Further information about storage conditions:**

Keep container tightly closed in a well-ventilated place.

· **Storage class**

8A

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require**

monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

CAS: 100-51-6 Benzyl alcohol

| | | |
|--------|------|-----------------------------------------------|
| Oral | DNEL | 4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark) |
| Dermal | DNEL | 8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark) |

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 4)

| | | |
|---------------------------------------------------------|------|-------------------------------------------------------------|
| Inhalative | DNEL | 22 mg/m ³ (ArL) 110 mg/m ³ (Ark) |
| CAS: 15520-10-2 2-methylpentane-1,5-diamine | | |
| Dermal | DNEL | 1.5 mg/kg bw/day (ArL) |
| Inhalative | DNEL | 0.25 mg/m ³ (ArL) 0.5 mg/m ³ (Ark) |
| CAS: 112-57-2 3,6,9-triazaundecamethylenediamine | | |
| Oral | DNEL | 0.53 mg/kg bw/Tag (ArL) |
| Dermal | DNEL | 0.74 mg/kg bw/day (ArL) |
| Inhalative | DNEL | 6940 mg/m ³ (ArL) |

· PNECs

CAS: 100-51-6 Benzyl alcohol

| | |
|------|---------------------------------------------------------------------------------------|
| PNEC | 0.527 mg/l (Marine water sediment) 0.1 mg/l (Mew) 1 mg/l (Fresh water sediment) |
| PNEC | 0.456 mg/kg dwt (Bod) 5.27 mg/kg dwt (Fresh water sediment) |

CAS: 15520-10-2 2-methylpentane-1,5-diamine

| | |
|------|--------------------------------------------|
| PNEC | 0.042 mg/l (Mew) 0.42 mg/l (Freshwater) |
|------|--------------------------------------------|

CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

| | |
|------|---------------------------------------------------------------------|
| PNEC | 9.73 mg/l (BEL) 0.0068 mg/l (Fresh water) 0.0068 mg/l (Mew) |
| PNEC | 0.343 mg/kg dwt (Sediment) 3.43 mg/kg dwt (Fresh water sediment) |

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

· Breathing equipment:

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 5)

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Nitrile rubber

Recommended material thickness: ≥ 0.4 mm

· Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm

Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm

Penetration time: ≥ 480 min

· Eye/face protection

Tight-fitting safety goggles.

Safety goggles.

· Body protection:

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· **Colour:**

Yellowish

· **Smell:**

Amine-like

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

205 °C

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 6)

| | |
|------------------------------------------|----------------------------------|
| · Lower and upper explosion limit | |
| · Lower: | 1.3 Vol % |
| · Upper: | 13 Vol % |
| · Flash point: | ≥61 °C |
| · Auto-ignition temperature: | 435 °C |
| · pH at 20 °C | 12 |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · dynamic at 20 °C: | 480 mPas |
| · Solubility | |
| · Water: | Not miscible or difficult to mix |
| · Steam pressure at 20 °C: | 0.1 hPa |
| · Density and/or relative density | |
| · Density at 20 °C | 1.04 g/cm ³ |

· 9.2 Other information

| | |
|----------------------------------------------------------------------------------------|------------------------------|
| · Appearance: | |
| · Form: | Fluid |
| · Important information on protection of health and environment, and on safety. | |
| · Self-inflammability: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. |

· Information with regard to physical hazard classes

| | |
|-----------------------------------------------------------------------------|------|
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | Void |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Void |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

| | |
|-------------------|--------------------------------------------|
| · 10.1 Reactivity | No further relevant information available. |
|-------------------|--------------------------------------------|

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 7)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 100-51-6 Benzyl alcohol

| | | |
|------------|----------------------|---------------------|
| Oral | LD50 | 1230 mg/kg (rat) |
| | NOAEL 2nd year study | 200 mg/kg (mouse) |
| Dermal | LD50 | 200 mg/kg (rat) |
| | LD50 | 2000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >4178 mg/l (rat) |

CAS: 15520-10-2 2-methylpentane-1,5-diamine

| | | |
|------------|----------|---------------------|
| Oral | LD50 | 1170 mg/kg (rat) |
| Dermal | LD50 | 1870 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 19.6 mg/l (rat) |

CAS: 69-72-7 salicylic acid

| | | |
|--------|------|-------------------|
| Oral | LD50 | 891 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |

CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

| | | |
|--------|------|---------------------|
| Oral | LD50 | 2140 mg/kg (rat) |
| Dermal | LD50 | 1260 mg/kg (rabbit) |

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 8)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 69-72-7 salicylic acid

List II; III

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 100-51-6 Benzyl alcohol

IC50/72h 700 mg/l (algae)

LC50/96h 460 mg/l (*Pimephales promelas*)

10 mg/l (*Lepomis macrochirus*)

CAS: 15520-10-2 2-methylpentane-1,5-diamine

EC50/72h >100 mg/l (algae)

EC50 1825 mg/l (fish)

EC50/48h 19.8 mg/l (*Daphnia magna*)

CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

EC50/72h 2.1 mg/l (algae)

LC50/96h 420 mg/l (*Gup*)

EC50/48h 24.1 mg/l (*Daphnia magna*)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 9)

- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

| | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| · 14.1 UN number or ID number · ADR, IMDG, IATA | UN2735 |
| · 14.2 UN proper shipping name · ADR, IMDG, IATA | AMINES, LIQUID, CORROSIVE, N.O.S. (2-methylpentane-1,5-diamine) |
| · 14.3 Transport hazard class(es) · ADR · Class · Label | 8 (C7) Corrosive substances. 8 |
| · IMDG, IATA · Class · Label | 8 Corrosive substances. 8 |
| · 14.4 Packing group · ADR, IMDG, IATA | II |
| · 14.5 Environmental hazards: · Marine pollutant: | No |
| · 14.6 Special precautions for user · Kemler Number: · EMS Number: · Segregation groups · Stowage Category · Segregation Code | Warning: Corrosive substances. 80 F-A, S-B (SGG18) Alkalis A SG35 Stow "separated from" SGG1-acids |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · Transport/Additional information: · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code | 1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 E |

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 10)

| | |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------|
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (2-METHYLPENTANE-1,5-DIAMINE), 8, II |

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture**

No further relevant information available.

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.
- H411 Toxic to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

Environment protection department.

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 27 (replaces version 26)

Revision: 09.03.2024

Trade name MC-DUR 1390 VK - Komponente B

(Contd. of page 11)

- **Abbreviations and acronyms:** RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

- * **Data compared to the previous version altered.**

GB