



BE SURE. BUILD SURE.

Page 1/13

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **MC-DUR 1900 Plus - Komponente A**

Article number: 2870

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Coating  
Epoxy coating

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

#### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS07 GHS09

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

**Trade name MC-DUR 1900 Plus - Komponente A**

(Contd. of page 1)

<ul style="list-style-type: none"> <li>· <b>Signal word</b></li> <li>· <b>Hazard-determining components of labelling:</b></li> <li>· <b>Hazard statements</b></li> <li>· <b>Precautionary statements</b></li> <li>· <b>Additional information:</b></li> <li>· <b>2.3 Other hazards</b></li> <li>· <b>Results of PBT and vPvB assessment</b></li> </ul>	<p><i>Warning</i></p> <p>Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)] dioxirane epoxide derivates Polymer with epoxy-functional groups 1,6-hexene-diglycidylether Reaktionsprodukt aus polyether-modifiziertem Polysiloxan und 6-Hexandiglycidylether</p> <p>H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.</p> <p>P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P273 Avoid release to the environment. P280 Wear protective gloves / eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.</p> <p>EUH205 Contains epoxy constituents. May produce an allergic reaction. EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.</p>				
<ul style="list-style-type: none"> <li>· <b>PBT:</b></li> <li>· <b>vPvB:</b></li> </ul>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">CAS: 541-02-6</td> <td>2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane</td> </tr> <tr> <td>CAS: 541-02-6</td> <td>2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane</td> </tr> </table>	CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane				
CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane				

**SECTION 3: Composition/information on ingredients**

· **3.2 Mixtures**  
· **Description:** Resin mixture with colouring agents.  
Mixture consisting of the following components.

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/13

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

Trade name **MC-DUR 1900 Plus - Komponente A**

(Contd. of page 2)

**· Dangerous components:**

CAS: 9003-36-5 EC number: 701-263-0	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥25-≤30%
CAS: 1675-54-3 EINECS: 216-823-5	epoxide derivates Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	≥10-<25%
EC number: 953-811-5	Polymer with epoxy-functional groups Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥10-<25%
CAS: 16096-31-4 EINECS: 240-260-4	1,6-hexene-diglycidylether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH205	≥2.5-<10%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	≥1-<5%
CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<3%
CAS: 2530-83-8 EINECS: 219-784-2	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318	≥1-<1.5%
CAS: 869858-05-9	Reaktionsprodukt aus polyether-modifiziertem Polysiloxan und 6-Hexandiglycidylether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥0.1-<1%
CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane Non-classified vPvB substance. Non-classified PBT substance. Substance identified as having endocrine disrupting properties (II).	<0.5%

**· SVHC**

CAS: 541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane

**· Additional information**

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****· 4.1 Description of first aid measures****· General information**

Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.

**· After inhalation**

Supply fresh air; seek medical advice if symptoms occur.

**· After skin contact**

If unconscious, place in recovery position and seek medical advice. In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.

**· After eye contact**

Rinse opened eye for several minutes under running water. Call a doctor immediately

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Page 4/13

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

Trade name **MC-DUR 1900 Plus - Komponente A**

· **After swallowing**

Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

(Contd. of page 3)

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** Use fire fighting measures that suit the environment.

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:**

No special measures required.

### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Not required.

· **6.2 Environmental precautions:**

Prevent material from reaching sewage system, holes and cellars.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· **6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

### SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Open and handle containers with care.

Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy

(Contd. on page 5)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

**Trade name MC-DUR 1900 Plus - Komponente A**

(Contd. of page 4)

resins. Open and handle containers with care.

- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Further information about storage conditions:** None.
- **Storage class** 12

**SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

**CAS: 16096-31-4 1,6-hexene-diglycidylether**

Dermal	DNEL	2.8 mg/kg bw/day (ArL)
Inhalative	DNEL	4.9 mg/m <sup>3</sup> (ArL)

**CAS: 100-51-6 Benzyl alcohol**

Oral	DNEL	4 mg/kg bw/Tag (ArL)
		20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL)
		40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m <sup>3</sup> (ArL)
		110 mg/m <sup>3</sup> (Ark)

· **PNECs**

**CAS: 16096-31-4 1,6-hexene-diglycidylether**

PNEC	0.0115 mg/l (Fresh water)
	0.00115 mg/l (Mew)
PNEC	0.223 mg/kg dwt (Bod)
	0.0283 mg/kg dwt (Sediment)
	0.283 mg/kg dwt (Fresh water sediment)

**CAS: 100-51-6 Benzyl alcohol**

PNEC	0.527 mg/l (Marine water sediment)
	0.1 mg/l (Mew)
	1 mg/l (Fresh water sediment)

(Contd. on page 6)



BE SURE. BUILD SURE.

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

Trade name **MC-DUR 1900 Plus - Komponente A**

(Contd. of page 5)

PNEC	0.456 mg/kg dwt (Bod)
	5.27 mg/kg dwt (Fresh water sediment)

- **Additional information:** *The lists that were valid during the compilation were used as basis.*
- **8.2 Exposure controls**
- **Appropriate engineering controls** *No further data; see section 7.*
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** *Keep away from food, drink and animal feed.  
Remove soiled, soaked clothing immediately.  
Wash hands before breaks and at the end of work.  
Avoid contact with eyes and skin.*
- **Breathing equipment:** *If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.*
- **Hand protection** *Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*
- **Material of gloves** *You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>  
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.  
Nitrile rubber  
Recommended material thickness:  $\geq 0.4$  mm*
- **Penetration time of glove material** *The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.  
The following applies to all other gloves:  
The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.  
Nitrile rubber  
Material thickness:  $\geq 0.40$  mm  
Penetration time:  $\geq 480$  min  
Butyl rubber:  
Material thickness:  $\geq 0.5$  mm  
Penetration time:  $\geq 480$  min*
- **Eye/face protection** *Tight-fitting safety goggles.  
Safety goggles.*

(Contd. on page 7)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 6)

· **Body protection:** *Protective clothing*  
*Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.*

#### SECTION 9: Physical and chemical properties

##### · 9.1 Information on basic physical and chemical properties

###### · General Information

· <b>Colour:</b>	Various colours
· <b>Smell:</b>	Fruit-like
· <b>Melting point/freezing point:</b>	Not determined
· <b>Boiling point or initial boiling point and boiling range</b>	>200 °C (CAS: 9003-36-5 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700)
· <b>Flash point:</b>	Not applicable
· <b>pH at 20 °C</b>	7
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>dynamic at 20 °C:</b>	11400 mPas
· <b>Solubility</b>	
· <b>Water:</b>	Not miscible or difficult to mix
· <b>Steam pressure at 20 °C:</b>	<0.1 hPa (CAS: 25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues molecular weight < 700)
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C</b>	1.33 g/cm <sup>3</sup>

##### · 9.2 Other information

· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive.

##### · Information with regard to physical hazard classes

· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void

(Contd. on page 8)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

**Trade name MC-DUR 1900 Plus - Komponente A**

(Contd. of page 7)

· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane**

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

**CAS: 1675-54-3 epoxide derivates**

Dermal	LD50	23000 mg/kg (rabbit)
--------	------	----------------------

**CAS: 16096-31-4 1,6-hexene-diglycidylether**

Oral	LD50	>8500 mg/kg (rat)
Dermal	LD50	>4900 mg/kg (rat)

(Contd. on page 9)





BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

**Trade name MC-DUR 1900 Plus - Komponente A**

(Contd. of page 8)

**CAS: 13463-67-7 titanium dioxide**

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)

**CAS: 100-51-6 Benzyl alcohol**

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

**CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane**

Oral	LD50	8030 mg/kg (rat)
Dermal	LD50	4248 mg/kg (rabbit)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II
CAS: 556-67-2	Octamethylcyclotetrasiloxane	List II; III
CAS: 556-67-2	octamethylcyclotetrasiloxane	List II; III
CAS: 128-37-0	2,6-Di-tert-butyl-p-cresol	List II

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane**

LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)

**CAS: 1675-54-3 epoxide derivates**

IC50	>42.6 mg/l (Bak)
------	------------------

(Contd. on page 10)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

**Trade name MC-DUR 1900 Plus - Komponente A**

(Contd. of page 9)

LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)
<b>CAS: 16096-31-4 1,6-hexene-diglycidylether</b>	
LC50/96h	30 mg/l (Leucidus idus)
EC50/48h	47 mg/l (Daphnia magna)
<b>CAS: 100-51-6 Benzyl alcohol</b>	
IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)
	10 mg/l (Lepomis macrochirus)
<b>CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane</b>	
LC50/96h	55 mg/l (Cyp)
EC50/48h	473 mg/l (Daphnia magna)
ErC50/72h	255 mg/l (Scenedesmus subspicatus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**

· **PBT:**

CAS: 541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane

· **vPvB:**

CAS: 541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane

- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Additional ecological information:**

- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.

**SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 10)

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

#### SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN3082

· **14.2 UN proper shipping name**

· **ADR, IATA**

ENVIRONMENTALLY HAZARDOUS  
SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)

· **IMDG**

ENVIRONMENTALLY HAZARDOUS  
SUBSTANCE, LIQUID, N.O.S. (epoxide derivates),  
MARINE POLLUTANT

· **14.3 Transport hazard class(es)**

· **ADR**

· **Class**

9 (M6) Miscellaneous dangerous substances and  
articles.

· **Label**

9

· **IMDG, IATA**

· **Class**

9 Miscellaneous dangerous substances and  
articles.

· **Label**

9

· **14.4 Packing group**

· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**

· **Marine pollutant:**

Yes

Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **Special marking (IATA):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Miscellaneous dangerous substances and  
articles.

· **Kemler Number:**

90

· **EMS Number:**

F-A, S-F

· **Stowage Category**

A

· **14.7 Maritime transport in bulk according to  
IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

(Contd. on page 12)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

Trade name MC-DUR 1900 Plus - Komponente A

(Contd. of page 11)

·	ml
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	(-)
<hr/>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III

#### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations**

· **Substances of very high concern (SVHC) according to UK REACH**

CAS: 541-02-6 | 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 16.03.2024

Version number 36 (replaces version 35)

Revision: 16.03.2024

Trade name **MC-DUR 1900 Plus - Komponente A**

(Contd. of page 12)

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
  - H302 Harmful if swallowed.
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.
  - H318 Causes serious eye damage.
  - H319 Causes serious eye irritation.
  - H332 Harmful if inhaled.
  - H351 Suspected of causing cancer.
  - H411 Toxic to aquatic life with long lasting effects.
  - H412 Harmful to aquatic life with long lasting effects.
  - EUH205 Contains epoxy constituents. May produce an allergic reaction.
  
- **Department issuing data specification sheet:** Environment protection department.
- **Abbreviations and acronyms:**
  - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
  - ICAO: International Civil Aviation Organisation
  - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - DNEL: Derived No-Effect Level (UK REACH)
  - PNEC: Predicted No-Effect Concentration (UK REACH)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - Acute Tox. 4: Acute toxicity – Category 4
  - Skin Irrit. 2: Skin corrosion/irritation – Category 2
  - Eye Dam. 1: Serious eye damage/eye irritation – Category 1
  - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
  - Skin Sens. 1: Skin sensitisation – Category 1
  - Carc. 2: Carcinogenicity – Category 2
  - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
  - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- \* Data compared to the previous version altered.

GB