



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024

Version number 32 (replaces version 31)

Revision: 05.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR 3500 FA - Komponente B**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

1.3 Application of the substance / the mixture

Mineral coating
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024

Version number 32 (replaces version 31)

Revision: 05.04.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** methyl methacrylate
butyl acrylate
N-Hydroxyethyl-N-methyl-p-toluidine
- **Hazard statements** H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
- **Precautionary statements**
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	60-80%
CAS: 141-32-2 EINECS: 205-480-7	butyl acrylate Flam. Liq. 3, H226; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥20-≤30%
CAS: 2082-81-7 EINECS: 218-218-1	tetramethylene dimethacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<2.5%

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024

Version number 32 (replaces version 31)

Revision: 05.04.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 2)

CAS: 2842-44-6 EINECS: 220-638-5	N-Hydroxyethyl-N-methyl-p-toluidine Eye Irrit. 2, H319; Skin Sens. 1, H317	≥1-<2.5%
CAS: 128-37-0 EINECS: 204-881-4	Butylated hydroxytoluene Skin Irrit. 2, H315; Eye Irrit. 2, H319	<0.5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **General information** Immediately remove any clothing contaminated with the product.
- **After inhalation** Supply fresh air and call for doctor for safety reasons.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Seek medical treatment.
- **After swallowing** Do not induce vomiting; instantly call for medical help.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· For safety reasons unsuitable extinguishing agents

Water with a full water jet.

· 5.2 Special hazards arising from the substance or mixture

Can be released in case of fire
Carbon monoxide (CO)

· 5.3 Advice for firefighters

- **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars. Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024

Version number 32 (replaces version 31)

Revision: 05.04.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 3)

See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** The product is not flammable
Fumes can combine with air to form an explosive mixture.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store only in the original container.
Store in cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
Protect from heat and direct sunlight.
- **Storage class** 3

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with critical values that require monitoring at the workplace:

CAS: 80-62-6 methyl methacrylate

WEL	Short-term value:	416 mg/m ³ , 100 ppm
	Long-term value:	208 mg/m ³ , 50 ppm

CAS: 141-32-2 butyl acrylate

WEL	Short-term value:	26 mg/m ³ , 5 ppm
	Long-term value:	5 mg/m ³ , 1 ppm

DNELs

CAS: 128-37-0 Butylated hydroxytoluene

Dermal	DNEL	8.3 mg/kg bw/day (ArL)
Inhalative	DNEL	5.8 mg/m ³ (ArL)

PNECs

CAS: 128-37-0 Butylated hydroxytoluene

PNEC aqua	0.4 µg/l (Mew)
-----------	----------------

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024

Version number 32 (replaces version 31)

Revision: 05.04.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 4)

	4 µg/l (Freshwater)
PNEC	100 mg/l (Sewage Treatment Plant)
PNEC	1.04 mg/kg dwt (Bod)
	1.29 mg/kg dwt (Sediment)

- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.
- **Breathing equipment:** Use breathing protection in case of insufficient ventilation.
Self-contained breathing apparatus.
Filter AX.
- **Hand protection** Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.
- **Material of gloves** Nitrile rubber, NBR
Butyl rubber, BR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material** The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.
- **Eye/face protection** Not required.
- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** Transparent
- **Smell:** Unpleasant
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** 101 °C

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024

Version number 32 (replaces version 31)

Revision: 05.04.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 5)

<ul style="list-style-type: none"> · Lower and upper explosion limit · Lower: 1.2 Vol % · Upper: 12.5 Vol % · Flash point: 10 °C · Auto-ignition temperature: 275 °C · pH Not determined. · Viscosity: · Kinematic viscosity at 20 °C 21 s (ISO 3 mm) · dynamic: Not determined. · Solubility · Water: Not miscible or difficult to mix · Steam pressure at 20 °C: 47 hPa · Density and/or relative density · Density at 20 °C 0.93 g/cm³ 	
<ul style="list-style-type: none"> · 9.2 Other information SAPT > 55°C · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/steam mixtures is possible. 	
<ul style="list-style-type: none"> · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Highly flammable liquid and vapour. · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void 	

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024

Version number 32 (replaces version 31)

Revision: 05.04.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 6)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** self-accelerating polymerization temperature => 100°C
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 80-62-6 methyl methacrylate

Oral	LD50	>6000 mg/kg (Rat)
Dermal	LD50	>7550 mg/kg (rabbit)

CAS: 141-32-2 butyl acrylate

Oral	LD50	900 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

CAS: 128-37-0 Butylated hydroxytoluene

Oral	LD50	>2930 mg/kg (rat)
	NOAEL	100 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
		>2000 mg/kg (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 128-37-0 Butylated hydroxytoluene

List II

GB

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024

Version number 32 (replaces version 31)

Revision: 05.04.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 7)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 80-62-6 methyl methacrylate

EC50/24h 502 mg/l (*Daphnia magna*)

LC50/96h 130 mg/l (*Pimephales promelas*)

191 mg/l (*Lepomis macrochirus*)

EC50/48h 69 mg/l (*Daphnia magna*)

CAS: 128-37-0 Butylated hydroxytoluene

EC50/72h 0.5 mg/l (*Desmodesmus subspicatus*)

EC50 >10000 mg/l (BEL)

LC50/48h 0.61 mg/l (*Daphnia magna*)

NOEC 0.07 mg/l (*Daphnia magna*)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

Not applicable.

vPvB:

Not applicable.

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA

UN1247

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024

Version number 32 (replaces version 31)

Revision: 05.04.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 8)

· 14.2 UN proper shipping name · ADR, IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED solution
· 14.3 Transport hazard class(es) · ADR · Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA · Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category · Stowage Code	Warning: Flammable liquids. 33 F-E, S-D C SW1 Protected from sources of heat. SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION, 3, II

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024

Version number 32 (replaces version 31)

Revision: 05.04.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 9)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H225 Highly flammable liquid and vapour.
 - H226 Flammable liquid and vapour.
 - H302 Harmful if swallowed.
 - H312 Harmful in contact with skin.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H335 May cause respiratory irritation.

· Department issuing data specification sheet: Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association

(Contd. on page 11)



BE SURE. BUILD SURE.

Page 11/11

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024

Version number 32 (replaces version 31)

Revision: 05.04.2024

Trade name MC-DUR 3500 FA - Komponente B

(Contd. of page 10)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

*** Data compared to the
previous version altered.**

GB