

Page 1/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024 Version number 33 (replaces version 32) Revision: 05.04.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name MC-DUR 3502 - Komponente A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture Special priming

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400

Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

#### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to

**Regulation (EC) No 1272/2008** The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining

components of labelling: methyl methacrylate

N-Hydroxyethyl-N-methyl-p-toluidine

(Contd. on page 2)



Page 2/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024 Version number 33 (replaces version 32) Revision: 05.04.2024

#### Trade name MC-DUR 3502 - Komponente A

(Contd. of page 1)

· **Hazard statements** H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

• Precautionary statements P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P241 Use explosion-proof [electrical/ventilating/

lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/

spray.

P280 Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water [or

shower].

P403+P233 Store in a well-ventilated place. Keep container

tightly closed.

· 2.3 Other hazards

· Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:				
CAS: 80-62-6	methyl methacrylate	80-100%		
EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335			
CAS: 2082-81-7	tetramethylene dimethacrylate	<10%		
EINECS: 218-218-1	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335			
CAS: 2842-44-6	N-Hydroxyethyl-N-methyl-p-toluidine	≥0.1-<1%		
EINECS: 220-638-5	Eye Irrit. 2, H319; Skin Sens. 1, H317			

#### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

General information Immediately remove any clothing contaminated with the product.

After inhalation Supply fresh air and call for doctor for safety reasons.
 After skin contact Instantly wash with water and soap and rinse thoroughly.
 After eye contact Rinse opened eye for several minutes under running water.

Seek medical treatment.

(Contd. on page 3)



Page 3/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024 Version number 33 (replaces version 32) Revision: 05.04.2024

Trade name MC-DUR 3502 - Komponente A

(Contd. of page 2)

• After swallowing Do not induce vomiting; instantly call for medical help.

### **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

· Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with

water jet or alcohol-resistant foam.

· For safety reasons unsuitable

extinguishing agents

Water with a full water jet.

• 5.2 Special hazards arising from the substance or

mixture

Can be released in case of fire

Nitrogen oxides (NOx) Carbon monoxide (CO)

· 5.3 Advice for firefighters

· Protective equipment:

Put on breathing apparatus.

#### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies. Prevent material from reaching sewage system, holes and cellars. Inform respective authorities in case product reaches water or

sewage system.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

# SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection

against explosions and fires: Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

The product is not flammable

(Contd. on page 4)



Page 4/10

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 05.04.2024 Printing date 05.04.2024 Version number 33 (replaces version 32)

#### Trade name MC-DUR 3502 - Komponente A

(Contd. of page 3)

Fumes can combine with air to form an explosive mixture.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: Store in cool location.

Store only in the original container.

Information about storage in

one common storage facility: Not required.

Further information about

storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

· Storage class

#### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

The lists that were valid during the compilation were used as basis. · Additional information:

· 8.2 Exposure controls Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from foodstuffs, beverages and food.

> Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Breathing equipment: Filter AX.

> In case of brief exposure or low pollution or when application is performed at confined area with adequate mechanical ventilation meeting local authority requirements, use breathing filter apparatus. In case of intensive or longer exposure use breathing

apparatus that is independent of circulating air.

· Hand protection Protective gloves.

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be (Contd. on page 5)



Page 5/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024 Version number 33 (replaces version 32) Revision: 05.04.2024

#### Trade name MC-DUR 3502 - Komponente A

(Contd. of page 4)

calculated in advance and has therefore to be checked prior to the

application.

· Penetration time of glove

material The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

· Eye/face protection Not required.

Body protection: Protective work clothing.

### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: Colourless
 Smell: Unpleasant
 Melting point/freezing point: -48 °C

Boiling point or initial boiling point and

boiling range 101 °C

· Lower and upper explosion limit

Lower: 2.1 Vol %
Upper: 12.5 Vol %
Flash point: 10 °C
Auto-ignition temperature: 430 °C

PH Not determined.

Viscosity:

• Kinematic viscosity
• dynamic at 20 °C:

Not determined.
300 mPas

·Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: 47 hPa

Density and/or relative density

Density at 20 °C 0.99 g/cm³

• 9.2 Other information SAPT > 55°C

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

• Explosive properties: Product is not explosive. However, formation of

explosive air/steam mixtures is possible.

· Information with regard to physical hazard

classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Void
Void

Flammable liquids Highly flammable liquid and vapour.

(Contd. on page 6)



Page 6/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024 Version number 33 (replaces version 32) Revision: 05.04.2024

#### Trade name MC-DUR 3502 - Komponente A

Contd.	of	nage	5
Conta.	UI	vauc	J

· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

### SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

**conditions to be avoided:** No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

• 10.4 Conditions to avoid self-accelerating polymerization temperature => 100°C

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

### **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

CAS: 80-62-6 methyl methacrylate

Oral LD50 >6000 mg/kg (Rat) Dermal LD50 >7550 mg/kg (rabbit)

· Skin corrosion/irritation Causes skin irritation.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Based on available data, the classification criteria are not met.
 Reproductive toxicity
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

STOT-single exposure May cause respiratory irritation.

• STOT-repeated exposure
• Aspiration hazard

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

(Contd. on page 7)



Page 7/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024 Version number 33 (replaces version 32) Revision: 05.04.2024

#### Trade name MC-DUR 3502 - Komponente A

(Contd. of page 6)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

# **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 80-62-6 methyl methacrylate

EC50/24h | 502 mg/l (Daphnia magna)

LC50/96h | 130 mg/l (Pimephales promelas)

191 mg/l (Lepomis macrochirus)

EC50/48h 69 mg/l (Daphnia magna)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

#### SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

### **SECTION 14: Transport information**

· 14.1 UN number or ID number

· **ADR, IMDG, IATA** UN1247

(Contd. on page 8)



Page 8/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024 Version number 33 (replaces version 32) Revision: 05.04.2024

# Trade name MC-DUR 3502 - Komponente A

	(Contd. of page
· 14.2 UN proper shipping name · ADR, IMDG, IATA	METHYL METHACRYLATE MONOMER STABILIZED
14.3 Transport hazard class(es)	
ADR Class Label	3 (F1) Flammable liquids. 3
· IMDG, IATA · Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	II .
· 14.5 Environmental hazards: · Marine pollutant:	no No
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category · Stowage Code	Warning: Flammable liquids. 33 F-E,S-D C SW1 Protected from sources of heat. SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk accordii IMO instruments	<b>ng to</b> Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m 2
Tunnel restriction code Remarks:	D/E 1 kg Gebinde: LQ
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 m
UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOME STABILIZED, 3, II



Page 9/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024 Version number 33 (replaces version 32) Revision: 05.04.2024

Trade name MC-DUR 3502 - Komponente A

(Contd. of page 8)

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- Qualifying quantity (tonnes)

for the application of lowertier requirements

5000 t

Qualifying quantity (tonnes)

for the application of upper-

tier requirements

50000 t

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

· Department issuing data

specification sheet: Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
(Contd. on page 10)

--- GI



Page 10/10

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 05.04.2024 Version number 33 (replaces version 32) Revision: 05.04.2024

### Trade name MC-DUR 3502 - Komponente A

(Contd. of page 9)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

GB