

Page 1/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2024 Version number 24 (replaces version 23) Revision: 22.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name <u>MC-DUR GLW - Komponente A</u>

· Article number: 1202

· 1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Epoxy coating

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

· 1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

msds@mc-bauchemie.de

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

- · 2.2 Label elements
- Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS05 GHS07 GHS08

· Signal word

Danger

(Contd. on page 2)



Page 2/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 22.03.2024 Printing date 22.03.2024 Version number 24 (replaces version 23)

Trade name MC-DUR GLW - Komponente A

(Contd. of page 1)

Hazard-determining

components of labelling: Polymer Epoxidharz-Addukt

> crystalline silica Aminpolymer

3,6,9-triazaundecamethylenediamine

· Hazard statements H318 Causes serious eve damage. H317 May cause an allergic skin reaction.

H372 Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation.

P260 Do not breathe dust/fume/gas/mist/vapours/ · Precautionary statements

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor. P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it

before reuse.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Resin mixture with colouring agents.

Mixture consisting of the following components.

· Dangerous compo	nents:	
CAS: 14808-60-7	crystalline silica STOT RE 1, H372	10-30%
CAS: 260549-92-6	Polymer Epoxidharz-Addukt Eye Dam. 1, H318	≥3-<10%
CAS: 180583-06-6	Aminpolymer Skin Sens. 1, H317	≥1-<2.5%
CAS: 112-57-2 EINECS: 203-986-2	3,6,9-triazaundecamethylenediamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	≥0.1-<0.25%

· Additional information For the wording of the listed hazard phrases refer to section 16.



Page 3/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2024 Version number 24 (replaces version 23) Revision: 22.03.2024

Trade name MC-DUR GLW - Komponente A

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

· After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or

mixture No further relevant information available.

5.3 Advice for firefighters

· **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures

Not required.

6.2 Environmental

precautions: Prevent material from reaching sewage system, holes and cellars.

Dilute with much water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

GB



Page 4/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2024 Version number 24 (replaces version 23) Revision: 22.03.2024

Trade name MC-DUR GLW - Komponente A

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Open and handle containers with care.

Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground our parks) ventilation measures are required.

underground car parks) ventilation measures are required.

are required.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins. Open and handle containers with care.

Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: Protect from heat and direct sunlight.

· Storage class 6.1D

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require

values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

· DNELs

CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

Oral DNEL 0.53 mg/kg bw/Tag (ArL)
Dermal DNEL 0.74 mg/kg bw/day (ArL)
Inhalative DNEL 6940 mg/m³ (ArL)

PNECs

CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

PNEC 9.73 mg/l (BEL) 0.0068 mg/l (Fresh water) 0.0068 mg/l (Mew)

(Contd. on page 5)



Page 5/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 22.03.2024 Printing date 22.03.2024 Version number 24 (replaces version 23)

Trade name MC-DUR GLW - Komponente A

(Contd. of page 4)

PNEC 0.343 mg/kg dwt (Sediment)

3.43 mg/kg dwt (Fresh water sediment)

Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

Keep away from food, drink and animal feed. hygienic measures

Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

Breathing equipment: If workplace limit values cannot be complied with by ventilation

> measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/ white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

· Hand protection Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

· Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be

checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

· Penetration time of glove

material

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min

· Eye/face protection Tight-fitting safety goggles.

Safety goggles.

(Contd. on page 6)



Page 6/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2024 Version number 24 (replaces version 23) Revision: 22.03.2024

Trade name MC-DUR GLW - Komponente A

Protective clothing

(Contd. of page 5)

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Body protection:

· Colour: Grey

· Smell: Characteristic
· Melting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range 100 °C (CAS: 7732-18-5 water, distilled,

conductivity or of similar purity)

Flash point: Not applicable

· pH Not determined.

Viscosity:

· Kinematic viscosity
· dynamic:

Not determined.

Not determined.

· Solubility

· Water: Fully miscible

• Steam pressure at 20 °C: 23 hPa (CAS: 7732-18-5 water, distilled,

conductivity or of similar purity)

Density and/or relative density

Density at 20 °C 1.4 g/cm³

· 9.2 Other information

· Appearance:

Fluid

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives
· Flammable gases
· Aerosols
· Oxidising gases
· Cases under pressure
· Flammable liquids
· Flammable solids

Void
· Void

(Contd. on page 7)



Page 7/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2024 Version number 24 (replaces version 23) Revision: 22.03.2024

Trade name MC-DUR GLW - Komponente A

(Contd. of page 6)

Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	
		_

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

CAS: 112-57-2 3.6.9-triazaundecamethylenediamine

Oral LD50 2140 mg/kg (rat)
Dermal LD50 1260 mg/kg (rabbit)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Causes damage to the lung through prolonged or repeated

exposure. Route of exposure: Inhalation.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 8)



Page 8/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2024 Version number 24 (replaces version 23) Revision: 22.03.2024

Trade name MC-DUR GLW - Komponente A

(Contd. of page 7)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

EC50/72h | 2.1 mg/l (algae) LC50/96h | 420 mg/l (Gup)

EC50/48h 24.1 mg/l (Daphnia magna)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

12.5 Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

· Recommended cleaning

agent: Water, if necessary with cleaning agent.

GB



Page 9/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2024 Version number 24 (replaces version 23) Revision: 22.03.2024

Trade name MC-DUR GLW - Komponente A

(Contd. of page 8)

14.1 UN number or ID number	
ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name	
ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordi	ng to
IMO instruments	Not applicable.

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)



Page 10/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 22.03.2024 Printing date 22.03.2024 Version number 24 (replaces version 23)

Trade name MC-DUR GLW - Komponente A

(Contd. of page 9)

· Relevant phrases H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H318 Causes serious eve damage.

H372 Causes damage to organs through prolonged or repeated

exposure.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing data

specification sheet: Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

* * Data compared to the previous version altered.