

Page 1/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 30 (replaces version 29)

Revision: 12.04.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier	
 Trade name 1.2 Relevant identified uses of the sector of Use 	<u>MC-DUR TopSpeed SC - Komponente B</u> of the substance or mixture and uses advised against SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 Product category Process category Environmental release 	PC9a Coatings and paints, thinners, paint removers PROC10 Roller application or brushing
category	ERC8f Widespread use leading to inclusion into/onto article (outdoor) ERC11a Widespread use of articles with low release (indoor)
 Article category Application of the substance / the mixture 	AC13 Plastic articles
• 1.3 Details of the supplier of • Manufacturer/Supplier:	
 Informing department: 1.4 Emergency telephone number: 	msds@mc-bauchemie.de Tel.: +49 / (0)700 24112112 (MCR) Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008
Acute Tox. 4 H332 Harmful if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.
• 2.2 Label elements • Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. (Contd. on page 2)



Page 2/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 30 (replaces version 29)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed SC - Komponente B

(Contd. of page 1) Hazard pictograms · Signal word Warning · Hazard-determining components of labelling: Aliphatisches Polyisocyanat hexamethylene diisocyanate · Hazard statements H332 Harmful if inhaled. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. · Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. P312 P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. · Additional information: EUH204 Contains isocyanates. May produce an allergic reaction. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description:	Mixture consisting of the following components.	
Dangerous components:		
CAS: 28182-81-2	Aliphatisches Polyisocyanat Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	80-100%
CAS: 108-32-7 EINECS: 203-572-1	Propylene carbonate Eye Irrit. 2, H319	<2.5%
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37- 0000	hexamethylene diisocyanate Acute Tox. 3, H331; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: $C \ge 0.5 \%$ Skin Sens. 1; H317: $C \ge 0.5 \%$	<0.1%
Additional information	For the wording of the listed hazard phrases refer to sec	tion 16.

(Contd. on page 3)



Page 3/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 30 (replaces version 29)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed SC - Komponente B

(Contd. of page 2)

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information	Remove soiled, soaked clothing immediately.
· After inhalation	Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.
· After skin contact	In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
· After eye contact	Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.
· After swallowing	Do NOT induce vomiting. Rinse mouth with water. Medical attention required.
 4.2 Most important symptom 	15

 4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

 • 4.3 Indication of any immediate medical attention and special treatment needed Therapeutic measures: No information available.

SECTION 5: Firefighting measures

 5.1 Extinguishing media Suitable extinguishing agents 	CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
 5.2 Special hazards arising from the substance or 	
mixture	No further relevant information available.
5.3 Advice for firefighters	
 Protective equipment: 	No special measures required.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and 	
emergency procedures 6.2 Environmental	Not required.
precautions:	Inform respective authorities in case product reaches water or sewage system.
• 6.3 Methods and material for	
containment and cleaning up	: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
· 6.4 Reference to other	
sections	See Section 7 for information on safe handling
	See Section 8 for information on personal protection equipment. (Contd. on page 4)



Page 4/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 30 (replaces version 29)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed SC - Komponente B

See Section 13 for information on disposal.

(Contd. of page 3)

SECTION 7: Handling and storage

• 7.1 Precautions for safe	
handling	Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application. For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored. At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people. For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours. Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.
 Information about protection against explosions and fires: 	Keep ignition sources away - do not smoke. Protect from heat. Do not store near heat sources.
 7.2 Conditions for safe storage, including any incompatibilities Storage Requirements to be met by 	Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.
storerooms and containers:	Keep tightly closed in original packaging. Ventilate storage rooms well. Carefully close opened containers and store upright to prevent any leakage.
Information about atorsas in	Storage temperature >5°C and <30°C
 Information about storage in one common storage facility: Further information about 	May be stored together with hazardous substances of other classes up to 200 kg.
storage conditions: • Storage class • 7.3 Specific end use(s)	None. 10 No further relevant information available.

(Contd. on page 5)



Page 5/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 30 (replaces version 29)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed SC - Komponente B

(Contd. of page 4)

·Combone	ents with critical va	lues that require monitoring at the workplace:
•	-06-0 hexamethyler	
WEL Sho Lon	ort-term value: 0.07 n g-term value: 0.02 m ı; as -NCO	ng/m ³
DNELs		
CAS: 281	82-81-2 Aliphatisch	nes Polyisocyanat
Inhalative	DNEL 0.5 mg/m ³ (Workers) (long term local)
	1 mg/m³ (ke	i) (acute local eff)
CAS: 822	-06-0 hexamethyler	ne diisocyanate
Inhalative	DNEL 0.5 mg/m³ (/	ArL)
PNECs		
CAS: 281	82-81-2 Aliphatisch	nes Polyisocyanat
PNEC aqu	ua 12.7 μg/l (Daphni	ia magna) (marine)
PNEC	38.28 mg/l (kei) (STP)
CAS: 822	-06-0 hexamethyler	ne diisocyanate
PNEC	100 mg/l (Sewag	e Treatment Plant)
	0.0199 mg/l (Mev	v)
	0.199 mg/l (Fresl	
PNEC	8884 mg/kg dwt (
4455 mg/kg dwt (i		(Marine water sediment)
44551 mg/kg dwt (Fresh water sediment)		
· Ingredien	ts with biological l	imit values:
	-06-0 hexamethyler	ne diisocyanate
	umol creatinine/mol	
	edium: urine ampling time: At the	end of the period od exposure
	arameter: isocyanate	
	al information:	
Appropria controls Individua General p	sure controls ate engineering I protection measu protective and measures	No further data; see section 7. res, such as personal protective equipment Do not smoke, eat or drink while working. Have eye w
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		equipment ready. Do not inhale gases/vapours/aerosols. Avoid contact with eyes skin.



Page 6/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024 Version nu

Version number 30 (replaces version 29)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed SC - Komponente B

· Breathing equipment:	(Contd. of page 5) Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short- term work. If applicable, further recommendations for respiratory protection can be found in the appendix. In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended. An nicht ausreichend entlüfteten Arbeitsplätzen und bei Spritzverarbeitung Atemschutz erforderlich. Empfohlen werden Frischluftmaske oder für kurzzeitige Arbeiten Kompinationsfilter A2-P2.
• Hand protection • Material of gloves	Bei überempfindlichkeit der Atemwege (Asthma, chronische Bronchitis) wird vom Umgang mit dem Produkt abgeraten. Suitable materials for protective gloves; EN 374: Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluororubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Recommendation: Dispose of contaminated gloves. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from
 Penetration time of glove material Eye/face protection Body protection: 	manufacturer to manufacturer. Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min. Multi-layer glove - PE/EVAL/PE ; Breakthrough time ≥480 min. Wear safety goggles/face protection. Wear suitable protective clothing when working. In case of hypersensitivity of the skin, handling of the product is not recommended.

SECTION 9: Physical and chemical properties

General Information		
Colour:	Colourless	
Smell:	Characteristic	
Melting point/freezing point:	Not determined	
Boiling point or initial boiling point a	nd	
boiling range	Not determined	
Flash point:	180 °C	
pH .	Not determined.	
Viscosity:		
Kinematic viscosity	Not determined.	

GB



Page 7/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 30 (replaces version 29)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed SC - Komponente B

		(Contd. of page 6
dynamic:	Not determined.	
Solubility		
Water:	Not miscible or difficult to mix	
Steam pressure:	Not determined.	
Density and/or relative density		
Density at 20 °C	1.15 g/cm³	
9.2 Other information		
Appearance:		
Form:	Fluid	
Important information on protection of hea	alth	
and environment, and on safety.		
Self-inflammability:	Product is not selfigniting.	
Explosive properties:	Product is not explosive.	
Information with regard to physical haz classes Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

 10.1 Reactivity 10.2 Chemical stability Thermal decomposition / 	No further relevant information available.	
conditions to be avoided: 10.3 Possibility of hazardous	No decomposition if used according to specifications.	
reactions	Reacts with amines	
 10.4 Conditions to avoid 	No further relevant information available.	
 10.5 Incompatible materials: 	No further relevant information available.	
	(Contd. on page 8)	
	GB	, —



Page 8/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 30 (replaces version 29)

Revision: 12.04.2024

(Contd. of page 7)

GB

Trade name MC-DUR TopSpeed SC - Komponente B

 10.6 Hazardous decomposition products:

No dangerous decomposition products known

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008** • **Acute toxicity** Harmful if inhaled.

· LD/LC50 values that are relevant for classification:CAS: 28182-81-2 Aliphatisches PolyisocyanatOralLD50>2500 mg/kg (rat) (OECD 423)

Dermal LD50 >2000 mg/kg (rat) (OECD 402)

CAS: 108-32-7 Propylene carbonate

Oral LD50 >5000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rabbit)

CAS: 822-06-0 hexamethylene diisocyanate

LD50 738 mg/kg (rat) Oral Skin corrosion/irritation Based on available data, the classification criteria are not met. · Respiratory or skin May cause an allergic skin reaction. sensitisation · Germ cell mutagenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. · Carcinogenicity · Reproductive toxicity Based on available data, the classification criteria are not met. • STOT-single exposure May cause respiratory irritation. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met. · 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity				
· Aquatic toxicity:				
CAS: 28182-81-2 Aliphatisches Polyisocyanat				
ErC10/72h 370 mg/l (Desi	modesmus subspicatus) (EU C.3)			
ErC50/72h >1000 mg/l (Desmodesmus subspicatus) (EU C.3)				
 12.2 Persistence and degradability 12.3 Bioaccumulative 	No further relevant information available.			
potential	No further relevant information available.			
 12.4 Mobility in soil 	No further relevant information available.			
 12.5 Results of PBT and 	vPvB assessment			
· PBT:	Not applicable.			
		(Contd. on page 9)		



Page 9/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 30 (replaces version 29)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed SC - Komponente B

· vPvB:	(Contd. of page 8) (Contd. of page 8)
 12.6 Endocrine disrupting properties 	The product does not contain substances with endocrine disrupting properties.
 12.7 Other adverse effects 	
· Remark:	Harmful to fish
· Additional ecological informa	ation:
· General notes:	Harmful to aquatic organisms
	Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

 13.1 Waste treatment metho Recommendation 	ds Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 Uncleaned packagings: Recommendation: 	Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

 14.1 UN number or ID number ADR, ADN, IMDG, IATA 	Void	
 14.2 UN proper shipping name ADR, ADN, IMDG, IATA 	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
• 14.7 Maritime transport in bulk according to IMO instruments Not applicable.		
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/



Page 10/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 30 (replaces version 29)

Revision: 12.04.2024

(Contd. of page 9)

Trade name MC-DUR TopSpeed SC - Komponente B

 Iegislation specific for the substance or mixture No further relev
 Poisons Act

No further relevant information available.

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

• Reportable explosives precursors None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · 15.2 Chemical safety
- assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases	H302 H315 H317 H319 H331 H332 H334 H335 EUH204	Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic if inhaled. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Contains isocyanates. May produce an allergic reaction.
 Department issuing data specification sheet: Abbreviations and acronyms: 	Environment protection department.	

(Contd. on page 11)

GB



Page 11/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.04.2024

Version number 30 (replaces version 29)

Revision: 12.04.2024

Trade name MC-DUR TopSpeed SC - Komponente B

(Contd. of page 10)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* * Data compared to the previous version altered.

GB -