



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 23 (replaces version 22)

Revision: 02.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-Estrifan Color Protect Pro - Komponente A**

Article number: 4386

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Coating material

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS07 GHS09

Signal word

Warning

Hazard-determining

components of labelling:

Hexanedioic acid, polymer with 2-oxiranyl methyl neodecanoate

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 23 (replaces version 22)

Revision: 02.12.2023

Trade name MC-Estrifan Color Protect Pro - Komponente A

(Contd. of page 1)

- **Hazard statements**
2-methyl-2H-isothiazol-3-one
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
1,2-benzisothiazol-3(2H)-one
H317 May cause an allergic skin reaction.
- **Precautionary statements**
H411 Toxic to aquatic life with long lasting effects.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Contains biocidal products: 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

	Polyacrylate Aquatic Chronic 3, H412	≥10-<25%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	10-30%
CAS: 716336-43-5	Hexanedioic acid, polymer with 2-oxiranyl methyl neodecanoate Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Skin Sens. 1B, H317	≥1-<2.5%
CAS: 5131-66-8 EINECS: 225-878-4	3-butoxypropan-2-ol Acute Tox. 3, H331; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<0.5%
CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥0.05 %	<0.05%

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 23 (replaces version 22)

Revision: 02.12.2023

Trade name MC-Estrifan Color Protect Pro - Komponente A

(Contd. of page 2)

CAS: 2682-20-4 EINECS: 220-239-6	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥0.0015 %	≥0.0015-<0.025%
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314: C ≥0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025-<0.0015%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** No special measures required.
- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** The product is not skin irritating.
- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing** In case of persistent symptoms consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

- **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 23 (replaces version 22)

Revision: 02.12.2023

Trade name MC-Estrifan Color Protect Pro - Komponente A

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** No dangerous materials are released.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class** 12
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

CAS: 5131-66-8 3-butoxypropan-2-ol

Oral DNEL 8.75 mg/kg bw/Tag (ArL)

Dermal DNEL 44 mg/kg bw/day (ArL)

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 23 (replaces version 22)

Revision: 02.12.2023

Trade name MC-Estrifan Color Protect Pro - Komponente A

(Contd. of page 4)

Inhalative DNEL 270.5 mg/m³ (ArL)

· PNECs

CAS: 5131-66-8 3-butoxypropan-2-ol

PNEC 10 mg/l (Sewage Treatment Plant)

0.0525 mg/l (Mew)

0.525 mg/l (Freshwater)

PNEC 0.16 mg/kg dwt (Bod)

0.236 mg/kg dwt (Sediment)

2.36 mg/kg dwt (Fresh water sediment)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

· Breathing equipment:

Not required.

· Hand protection

Impervious gloves

· Material of gloves

Butyl rubber, BR

· Penetration time of glove material

-

· Eye/face protection

Safety glasses

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:

Various colours

· Smell:

Characteristic

· Melting point/freezing point:

Not determined

· Boiling point or initial boiling point and boiling range

100 °C

· Flash point:

Not applicable

· pH at 20 °C

7

· Viscosity:

· Kinematic viscosity

Not determined.

· dynamic at 20 °C:

4000 mPas

· Solubility

· Water:

Fully miscible

· Steam pressure at 20 °C:

23 hPa

· Density and/or relative density

· Density at 20 °C

1.3 g/cm³

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 23 (replaces version 22)

Revision: 02.12.2023

Trade name MC-Estrifan Color Protect Pro - Komponente A

(Contd. of page 5)

· **9.2 Other information**

· **Appearance:**

· **Form:**

Fluid

· **Important information on protection of health and environment, and on safety.**

· **Self-inflammability:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive.

· **Information with regard to physical hazard classes**

· **Explosives**

Void

· **Flammable gases**

Void

· **Aerosols**

Void

· **Oxidising gases**

Void

· **Gases under pressure**

Void

· **Flammable liquids**

Void

· **Flammable solids**

Void

· **Self-reactive substances and mixtures**

Void

· **Pyrophoric liquids**

Void

· **Pyrophoric solids**

Void

· **Self-heating substances and mixtures**

Void

· **Substances and mixtures, which emit flammable gases in contact with water**

Void

· **Oxidising liquids**

Void

· **Oxidising solids**

Void

· **Organic peroxides**

Void

· **Corrosive to metals**

Void

· **Desensitised explosives**

Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity**

No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions**

No dangerous reactions known

· **10.4 Conditions to avoid**

No further relevant information available.

· **10.5 Incompatible materials:**

No further relevant information available.

· **10.6 Hazardous**

decomposition products:

No dangerous decomposition products known

GB

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 23 (replaces version 22)

Revision: 02.12.2023

Trade name MC-Estrifan Color Protect Pro - Komponente A

(Contd. of page 6)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

CAS: 13463-67-7 titanium dioxide

Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)

CAS: 5131-66-8 3-butoxypropan-2-ol

Oral	LD50	3300 mg/kg (rat)
	NOAEL	350 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>3.4 mg/l (rat)

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

Oral	LD50	1020 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one

Oral	LD50	50-300 mg/kg (rat)
Inhalative	LC50/4 h	0.11 mg/l (rat)

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral	LD50	49.6-75 mg/kg (rat)
Dermal	LD50	87.12 mg/kg (rabbit)
Inhalative	LC50/4 h	0.171 mg/l (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

11.2 Information on other hazards

- **Endocrine disrupting properties**

None of the ingredients is listed.

GB

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 23 (replaces version 22)

Revision: 02.12.2023

Trade name MC-Estrifan Color Protect Pro - Komponente A

(Contd. of page 7)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 716336-43-5 Hexanedioic acid, polymer with 2-oxiranyl methyl neodecanoate

LC50/96h >0.072 mg/l (Danio rerio) (OECD 203)

CAS: 5131-66-8 3-butoxypropan-2-ol

LC0/96h >560 mg/l (Danio rerio) (OECD 203)
 LC50/96h >560 mg/l (Gup)
 EC50 >1000 mg/l (BEL)
 EC50/48h >1000 mg/l (Daphnia magna)
 NOEC 180 mg/l (Gup)
 560 mg/l (Selenastrum capricornutum)
 560 mg/l (Daphnia magna)

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

EC50/72h 0.067 mg/l (Pseudokirchneriella subcapitata)
 0.11 mg/l (Selenastrum capricornutum)
 LC50/96h 1.6 mg/l (Oncorhynchus mykiss)
 EC50/48h 1.1 mg/l (Daphnia magna)

CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one

EC50/72h 0.157 mg/l (Pseudokirchneriella subcapitata)
 LC50/96h 6 mg/l (Oncorhynchus mykiss)
 EC50/48h 1.68 mg/l (Daphnies)

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

LC50/24h 0.19 mg/l (fish)
 EC50/72h 0.027 mg/l (Pseudokirchneriella subcapitata)
 LC50/96h 0.19 mg/l (Oncorhynchus mykiss)
 LC50/48h 0.28 mg/l (fish)
 EC50/48h 0.16 mg/l (Daphnia magna)
 NOEC 0.02 mg/l (Oncorhynchus mykiss)
 0.00049 mg/l (Ske)
 0.1 mg/l (Daphnia magna)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

Not applicable.

vPvB:

Not applicable.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 23 (replaces version 22)

Revision: 02.12.2023

Trade name MC-Estrifan Color Protect Pro - Komponente A

(Contd. of page 8)

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:**

Disposal must be made according to official regulations.

· **Recommended cleaning agent:**

Water, if necessary with cleaning agent.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, ADN, IMDG, IATA**

Void

· **14.2 UN proper shipping name**

· **ADR, ADN, IMDG, IATA**

Void

· **14.3 Transport hazard class(es)**

· **ADR, ADN, IMDG, IATA**

· **Class**

Void

· **14.4 Packing group**

· **ADR, IMDG, IATA**

Void

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Not applicable.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

Not dangerous according to the above specifications.

· **UN "Model Regulation":**

Void

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 23 (replaces version 22)

Revision: 02.12.2023

Trade name MC-Estrifan Color Protect Pro - Komponente A

(Contd. of page 9)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture
- Poisons Act

No further relevant information available.

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

CAS: 7664-41-7 Ammonia, anhydrous

Listed

CAS: 50-00-0 formaldehyde

5%

- 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

- Department issuing data specification sheet:

Environment protection department.

- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 11)



BE SURE. BUILD SURE.

Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.12.2023

Version number 23 (replaces version 22)

Revision: 02.12.2023

Trade name MC-Estrifan Color Protect Pro - Komponente A

(Contd. of page 10)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

Carc. 2: Carcinogenicity – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the
previous version altered.**

GB