

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1 Product identifier

Trade name **MC-Estrifan IH - Komponente B**

Article number: 1448

##### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

##### Application of the substance / the mixture

Epoxy resin  
Injektion  
Hardening agent/ Curing agent

##### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

##### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

#### SECTION 2: Hazards identification

##### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4	H302 Harmful if swallowed.
Skin Corr. 1A	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H335 May cause respiratory irritation.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

##### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

**Trade name MC-Estrifan IH - Komponente B**

· **Hazard pictograms**



GHS05 GHS07

· **Signal word**

**Danger**

· **Hazard-determining components of labelling:**

2-methylpentane-1,5-diamine  
Isophorone diamine  
polymer amine terminated  
Benzyl alcohol

· **Hazard statements**

H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P260 Do not breathe dusts or mists.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

(Contd. of page 1)

### SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:**

Binding agent with colouring agents.  
Mixture consisting of the following components.

· **Dangerous components:**

CAS: 15520-10-2 EINECS: 239-556-6	2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	30-60%
CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥25-≤30%

(Contd. on page 3)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

**Trade name MC-Estrifan IH - Komponente B**

(Contd. of page 2)		
EC number: 949-140-2	polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	10-30%
CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	10-30%
CAS: 9046-10-0 Reg.nr.: 01-2119557899-12	Polyoxypropylenediamine Skin Corr. 1B, H314; Aquatic Chronic 3, H412	≥5-<10%
CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	≥1-<1.5%
CAS: 2855-13-2 EINECS: 220-666-8 Reg.nr.: 01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1A, H317 ATE: LD50 oral: 1030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥0.1-<0.5%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### · **4.1 Description of first aid measures**

- **General information** Immediately remove any clothing contaminated with the product. Take affected persons into the open air.
- **After inhalation** Supply fresh air.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Seek medical treatment.
- **After swallowing** Drink copious amounts of water and provide fresh air. Instantly call for doctor.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

GB

(Contd. on page 4)

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

**Trade name MC-Estrifan IH - Komponente B**

(Contd. of page 3)

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**      *Wear protective equipment. Keep unprotected persons away.*
- **6.2 Environmental precautions:**      *Prevent material from reaching sewage system, holes and cellars.*
- **6.3 Methods and material for containment and cleaning up:**      *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.*
- **6.4 Reference to other sections**      *See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.*

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**      *Store in cool, dry place in tightly closed containers.  
Open and handle container with care.*
- **Information about protection against explosions and fires:**      *No special measures required.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**      *No special requirements.*
- **Information about storage in one common storage facility:**      *Not required.*
- **Further information about storage conditions:**      *Keep container tightly sealed.*
- **Storage class**      *8A*

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:**      *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

#### · DNELs

**CAS: 15520-10-2 2-methylpentane-1,5-diamine**

Dermal	DNEL	1.5 mg/kg bw/day (ArL)
Inhalative	DNEL	0.25 mg/m <sup>3</sup> (ArL)

(Contd. on page 5)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

**Trade name MC-Estrifan IH - Komponente B**

(Contd. of page 4)

		0.5 mg/m³ (Ark)
<b>CAS: 2855-13-2 Isophorone diamine</b>		
Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
Inhalative	DNEL	20.1 mg/m³ (ArL)
<b>CAS: 100-51-6 Benzyl alcohol</b>		
Oral	DNEL	4 mg/kg bw/Tag (ArL)
		20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL)
		40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m³ (ArL)
		110 mg/m³ (Ark)
<b>CAS: 9046-10-0 Polyoxypropylenediamine</b>		
Oral	DNEL	0.04 mg/kg bw/Tag (ArL)
Dermal	DNEL	2.5 mg/kg bw/day (ArL)
<b>CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>		
Inhalative	DNEL	0.31 mg/m³ (ArL)
<b>CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine</b>		
Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
Inhalative	DNEL	20.1 mg/m³ (ArL)
<b>PNECs</b>		
<b>CAS: 15520-10-2 2-methylpentane-1,5-diamine</b>		
PNEC	0.042 mg/l (Mew)	
	0.42 mg/l (Freshwater)	
<b>CAS: 2855-13-2 Isophorone diamine</b>		
PNEC	0.006 mg/l (Mew)	
	0.06 mg/l (Freshwater)	
PNEC	0.578 mg/kg dwt (Sediment)	
	5.784 mg/kg dwt (Fresh water sediment)	
<b>CAS: 100-51-6 Benzyl alcohol</b>		
PNEC	0.527 mg/l (Marine water sediment)	
	0.1 mg/l (Mew)	
	1 mg/l (Fresh water sediment)	
PNEC	0.456 mg/kg dwt (Bod)	
	5.27 mg/kg dwt (Fresh water sediment)	
<b>CAS: 9046-10-0 Polyoxypropylenediamine</b>		
PNEC	7.5 mg/l (Sewage Treatment Plant)	
	0.015 mg/l (Fresh water)	
PNEC	0.0176 mg/kg dwt (Bod)	
	0.125 mg/kg dwt (Sediment)	

(Contd. on page 6)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

**Trade name MC-Estrifan IH - Komponente B**

(Contd. of page 5)

	0.132 mg/kg dwt (Fresh water sediment)
<b>CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>	
PNEC	0.2 mg/l (Sewage Treatment Plant)
	0.0084 mg/l (Mew)
	0.084 mg/l (Freshwater)
<b>CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine</b>	
PNEC	0.006 mg/l (Mew)
	0.06 mg/l (Freshwater)
PNEC	0.578 mg/kg dwt (Sediment)
	5.784 mg/kg dwt (Fresh water sediment)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.  
Instantly remove any soiled and impregnated garments.  
Wash hands during breaks and at the end of the work.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· **Hand protection**

Protective gloves.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

After use of gloves apply skin-cleaning agents and skin cosmetics.  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.

· **Eye/face protection**

Not required.

· **Body protection:**

Protective work clothing.

GB

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/13

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

Trade name MC-Estrifan IH - Komponente B

(Contd. of page 6)

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

· Colour:	Light yellow
· Smell:	Characteristic
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	Not determined
· Lower and upper explosion limit	
· Lower:	1.3 Vol %
· Upper:	13 Vol %
· Flash point:	111 °C
· Auto-ignition temperature:	380 °C
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity at 20 °C	19 s (DIN 53211/4)
· dynamic:	Not determined.
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 20 °C:	0.1 hPa
· Density and/or relative density	
· Density at 20 °C	1.01 g/cm <sup>3</sup>

#### · 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

#### · Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void

(Contd. on page 8)

GB



## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

**Trade name MC-Estrifan IH - Komponente B**

(Contd. of page 7)

· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.

· **LD/LC50 values that are relevant for classification:**

**CAS: 15520-10-2 2-methylpentane-1,5-diamine**

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

**CAS: 2855-13-2 Isophorone diamine**

Oral	LD50	1030 mg/kg (ATE)
		1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit)
		>2000 mg/kg (rat)

**CAS: 100-51-6 Benzyl alcohol**

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

**CAS: 9046-10-0 Polyoxypropylenediamine**

Oral	LD50	2855 mg/kg (Rat)
Dermal	LD50	2980 mg/kg (Kan)

(Contd. on page 9)



## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

**Trade name MC-Estrifan IH - Komponente B**

(Contd. of page 8)

**CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol**

Oral	LD50	mg/kg (rat)
	NOAEL	15 mg/kg (rat)

**CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine**

Oral	LD50	1030 mg/kg (ATE)
		1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit)
		>2000 mg/kg (rat)

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

## SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

**CAS: 15520-10-2 2-methylpentane-1,5-diamine**

EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (Daphnia magna)

**CAS: 2855-13-2 Isophorone diamine**

LC50/96h	110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodesmus subspicatus)
	3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodesmus subspicatus)

**CAS: 100-51-6 Benzyl alcohol**

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)

(Contd. on page 10)

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

**Trade name MC-Estrifan IH - Komponente B**

(Contd. of page 9)

	10 mg/l ( <i>Lepomis macrochirus</i> )
<b>CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol</b>	
EC50/72h	84 mg/l ( <i>Desmodesmus subspicatus</i> )
LC50/96h	175 mg/l ( <i>Cyp</i> )
	718 mg/l ( <i>Daphnia magna</i> )
NOEC	2 mg/l ( <i>BEL</i> )
	6.25 mg/l ( <i>Desmodesmus subspicatus</i> )
<b>CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine</b>	
LC50/96h	110 mg/l ( <i>Leucidus idus</i> )
EC50	1120 mg/l ( <i>Pseudomonas putida</i> )
EC50/48h	23 mg/l ( <i>Daphnia magna</i> )
NOEC	1.5 mg/l ( <i>Desmodesmus subspicatus</i> )
	3 mg/l ( <i>Daphnia magna</i> )
ErC50/72h	>50 mg/l ( <i>Desmodesmus subspicatus</i> )

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

GB

(Contd. on page 11)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

**Trade name MC-Estrifan IH - Komponente B**

(Contd. of page 10)

### SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN2735
· 14.2 UN proper shipping name	
· ADR, IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S. (2-methylpentane-1,5-diamine, Isophorone diamine)
· 14.3 Transport hazard class(es)	
· ADR	
· Class	8 (C7) Corrosive substances.
· Label	8
· IMDG, IATA	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Kemler Number:	80
· EMS Number:	F-A, S-B
· Segregation groups	(SGG18) Alkalies
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	E
· Remarks:	1 kg Gebinde: Begrenzte Mengen
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 12)

GB

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

**Trade name MC-Estrifan IH - Komponente B**

(Contd. of page 11)

· **UN "Model Regulation":** UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S.  
(2-METHYLPENTANE-1,5-DIAMINE,  
ISOPHORONE DIAMINE), 8, II

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture**

No further relevant information available.

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

**Safety data sheet**  
**according to Regulation (EC) No 1907/2006, Article 31**

Printing date 09.03.2024

Version number 22 (replaces version 21)

Revision: 09.03.2024

**Trade name MC-Estrifan IH - Komponente B**

(Contd. of page 12)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* Data compared to the  
previous version altered.

GB