

Page 1/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 21 (replaces version 20) Revision: 09.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name MC-Estrifan RIS - Komponente A

· Article number: 1315

· 1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Epoxy resin

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

1.4 Emergency telephone

number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

msds@mc-bauchemie.de

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP

regulation.

· Hazard pictograms





GHS07 GHS09

· Signal word

Warning

(Contd. on page 2)



Page 2/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 09.03.2024 Printing date 09.03.2024 Version number 21 (replaces version 20)

Trade name MC-Estrifan RIS - Komponente A

(Contd. of page 1)

Hazard-determining

components of labelling:

epoxide derivates

Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives

Reaction mass of 2.2'-[methylenebis(4.1-phenyleneoxymethylene)] dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]

dioxirane

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane

(1:2)

· Hazard statements H315 Causes skin irritation.

> H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical

advice/attention.

P337+P313 If eye irritation persists: Get medical advice/

attention.

· Additional information: EUH205 Contains epoxy constituents. May produce an allergic

reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Resin mixture with colouring agents.

Mixture consisting of the following components.

· Dangerous components:		
CAS: 1675-54-3	epoxide derivates	60-80%
EINECS: 216-823-5	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	
CAS: 100-51-6	Benzyl alcohol	10-30%
	Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	
	(C	ontd on page 3)



Page 3/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 21 (replaces version 20) Revision: 09.03.2024

Trade name MC-Estrifan RIS - Komponente A

	(C	contd. of page 2)
CAS: 68609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	10-30%
EINECS: 271-846-8	Skin Irrit. 2, H315; Skin Sens. 1, H317, EUH205	
CAS: 9003-36-5 EC number: 701-263-0	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<10%
CAS: 933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl) oxirane (1:2) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<2.5%
· Additional information	•	ection 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• After inhalation Supply fresh air.

After skin contact Instantly wash with water and soap and rinse thoroughly.
 After eye contact Rinse opened eye for several minutes under running water.

Seek medical treatment.

· After swallowing Rinse out mouth and then drink plenty of water.

Seek medical treatment.

· 4.2 Most important symptoms and effects, both acute and

delayed Allergic reactions

SECTION 5: Firefighting measures

5.1 Extinguishing media

• Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· For safety reasons unsuitable

extinguishing agents

Water with a full water jet.

5.2 Special hazards arising from the substance or

mixture Can be released in case of fire

Carbon monoxide (CO) Nitrogen oxides (NOx)

(Traces)

· 5.3 Advice for firefighters

· Protective equipment: Wear self-contained breathing apparatus.

GB



Page 4/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 21 (replaces version 20) Revision: 09.03.2024

Trade name MC-Estrifan RIS - Komponente A

(Contd. of page 3)

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures

· 6.2 Environmental

precautions:

Wear protective equipment. Keep unprotected persons away.

Inform respective authorities in case product reaches water or

sewage system.

Prevent material from reaching sewage system, holes and cellars.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Store in cool, dry place in tightly closed containers.

Open and handle container with care.

· Information about protection

against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: Store only in the original container.

· Information about storage in

one common storage facility: Store away from foodstuffs.

· Further information about

storage conditions: Keep container tightly sealed.

· Storage class 10

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

· DNELs

CAS: 100-51-6 Benzyl alcohol

Oral DNEL 4 mg/kg bw/Tag (ArL)

20 mg/kg bw/Tag (Ark)

(Contd. on page 5)



Page 5/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 21 (replaces version 20) Revision: 09.03.2024

Trade name MC-Estrifan RIS - Komponente A

			(Contd. of page 4)
Dermal	DNE	_ 8 mg/kg bw/day (ArL)	
		40 mg/kg bw/day (Ark)	
Inhalati	ve DNE	22 mg/m³ (ArL)	
		110 mg/m³ (Ark)	
CAS: 6	8609-97	2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	
Oral	DNE	1 mg/kg bw/Tag (ArL)	
Dermal	DNE	1.7 mg/kg bw/day (ArL)	
Inhalati	ve DNE	_ 0.98 mg/m³ (ArL)	
· PNECs	;		
CAS: 1	00-51-6	Benzyl alcohol	
PNEC	0.527 m	g/l (Marine water sediment)	
	0.1 mg/l	(Mew)	
	1 mg/l (l	resh water sediment)	
PNEC	0.456 mg/kg dwt (Bod)		
	5.27 mg/kg dwt (Fresh water sediment)		
CAS: 6	CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives		
PNEC	EC 0.00072 mg/l (Mew)		
	0.0072 mg/l (Freshwater)		
PNEC	80.12 m	g/kg dwt (Bod)	
	6.677 mg/kg dwt (Sediment)		
	66.77 mg/kg dwt (Fresh water sediment)		

· Additional information:

The lists that were valid during the compilation were used as basis.

8.2 Exposure controls
Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

· Material of gloves

hygienic measures Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

· Hand protection Protective gloves.

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics. The selection of the suitable gloves does not only depend on the

material, but also on further marks of quality and varies from

(Contd. on page 6)



Page 6/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 21 (replaces version 20) Revision: 09.03.2024

Trade name MC-Estrifan RIS - Komponente A

(Contd. of page 5)

manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

application.

· Penetration time of glove

material The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

· Eye/face protection Not required.

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Yellow

Smell: CharacteristicMelting point/freezing point: Not determined

Boiling point or initial boiling point and

>200 °C (CAS: 1675-54-3 bis[4-(2,3-

epoxypropoxy)phenyl]propane)

· Lower and upper explosion limit

Lower: 1.3 Vol % (CAS: 100-51-6 Benzyl alcohol)
 Upper: 13 Vol % (CAS: 100-51-6 Benzyl alcohol)

· Flash point: 101 °C

• Auto-ignition temperature: 400 °C (CAS: 68609-97-2 Oxirane, mono[(C12-

14-alkyloxy)methyl] derivatives)

PH Not determined.

· Viscosity:

Kinematic viscositydynamic at 20 °C:Not determined.1300 mPas

· Solubility

· Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: 0.1 hPa (CAS: 100-51-6 Benzyl alcohol)

· Vapour pressure at 50 °C: 0.7 hPa

Density and/or relative density

Density at 20 °C 1.14 g/cm³

· 9.2 Other information

· Appearance:

Fluid

· Important information on protection of health

and environment, and on safety.

· Self-inflammability: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/steam mixtures is possible.

(Contd. on page 7)



Page 7/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 21 (replaces version 20) Revision: 09.03.2024

Trade name MC-Estrifan RIS - Komponente A

(Contd. of page 6)

· Information with regard to physical haz classes	ard
Explosives	Void
· Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:		
CAS: 1675-54-3 epoxide derivates		
Dermal	LD50	23000 mg/kg (rabbit)
CAS: 100-51-6 Benzyl alcohol		
Oral	LD50	1230 mg/kg (rat)

(Contd. on page 8)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 21 (replaces version 20) Revision: 09.03.2024

Trade name MC-Estrifan RIS - Komponente A

	110151 0 1	(Contd. c	of page
	NOAEL 2nd year stud	ly 200 mg/kg (mouse)	
		200 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>4178 mg/l (rat)	
CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives			
Oral	LD50	17100 mg/kg (rat)	
CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane			
Oral	LD50	>2000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Skin corr	osion/irritation	Causes skin irritation.	
		Causes serious eye irritation.	
Respiratory or skin			
sensitisat	. •	May cause an allergic skin reaction.	~ t
		Based on available data, the classification criteria are not me	
		Based on available data, the classification criteria are not m Based on available data, the classification criteria are not m	
		Based on available data, the classification criteria are not mi Based on available data, the classification criteria are not mi	
		Based on available data, the classification criteria are not mi Based on available data, the classification criteria are not mi	
· Aspiration hazard Based on available data, the classification criteria are not met. · 11.2 Information on other hazards			
Endocrine disrupting properties		1:-1	
CAS: 128-	-37-0 2,6-Di-tert-butyl- _l	o-cresoi	List

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic to	<u> </u>	
CAS: 1675	-54-3 epoxide derivates	
IC50	>42.6 mg/l (Bak)	
LC50/96h	2 mg/l (Oncorhynchus mykiss)	
EC50/48h	1.8 mg/l (Daphnia magna)	
ErC50/72h	11 mg/l (Selenastrum capricornutum)	
CAS: 100-5	51-6 Benzyl alcohol	
IC50/72h	700 mg/l (algae)	
LC50/96h	460 mg/l (Pimephales promelas)	
	10 mg/l (Lepomis macrochirus)	
CAS: 6860	9-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives	
EbC50/72h	843 mg/l (Pseudokirchneriella subcapitata)	
LC50/96h	>5000 mg/l (Oncorhynchus mykiss)	
	(Contd. on pag	ge 🤉



Page 9/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 21 (replaces version 20) Revision: 09.03.2024

Trade name MC-Estrifan RIS - Komponente A

(Contd. of page 8)

1800 mg/l (Lepomis macrochirus)

EC50 >100 mg/l (BEL)

NOEC 500 mg/l (Pseudokirchneriella subcapitata)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

LC50/96h >100 mg/l (Daphnia magna) EC50/96h >100 mg/l (Leucidus idus)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Remark: Toxic for fish

· Additional ecological information:

General notes: Toxic for aquatic organisms

Also poisonous for fish and plankton in water bodies.

Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN3082

· 14.2 UN proper shipping name

ADR, IATA ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (epoxide derivates, Oxirane, mono[(C12-14-alkyloxy)methyl]

(Contd. on page 10)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 21 (replaces version 20) Revision: 09.03.2024

Trade name MC-Estrifan RIS - Komponente A

	(Contd. of pag
IMDG	derivatives) ENVIRONMENTALLY HAZARDOL SUBSTANCE, LIQUID, N.O.S. (epoxide derivate Oxirane, mono[(C12-14-alkyloxy)meth derivatives), MARINE POLLUTANT
14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous dangerous substances a articles.
Label	9
IMDG, IATA	
Class	9 Miscellaneous dangerous substances a articles.
Label	9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
On a sial manthing (ADD):	Symbol (fish and tree)
Special marking (ADR): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
· · · · · · · · · · · · · · · · · · ·	
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances a articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk accord	ina to
IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
- , ,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 10
To see a set of a set of a second	ml
Transport category	3
Tunnel restriction code Remarks:	(-) Regranzta Mangan
	Begrenzte Mengen
IMDG Limited quantities (LQ)	El
i imiton niiantitios (1 (.))	5L

(Contd. on page 11)



Page 11/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 09.03.2024 Printing date 09.03.2024 Version number 21 (replaces version 20)

Trade name MC-Estrifan RIS - Komponente A

	(Contd. of page 10)
· Excepted quantities (EQ) · Remarks:	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml LQ
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS
· ·	SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES, OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVATIVES), 9, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-

tier requirements

Qualifying quantity (tonnes) for the application of upper-

tier requirements

500 t

200 t

· 15.2 Chemical safety

A Chemical Safety Assessment has not been carried out. assessment:

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Harmful if swallowed. · Relevant phrases H302

> H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 12)



Page 12/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 21 (replaces version 20) Revision: 09.03.2024

Trade name MC-Estrifan RIS - Komponente A

(Contd. of page 11)

Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· Department issuing data

specification sheet:

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par

route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 3

* * Data compared to the previous version altered.

GB