

Page 1/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name MC-Flex 2098 - Komponente B

· Article number: 1254

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

Application of the substance

/ the mixture Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

msds@mc-bauchemie.de

1.4 Emergency telephone

number: Tel.: +

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Page 2/13

(Contd. of page 1)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

Trade name MC-Flex 2098 - Komponente B

· Hazard pictograms

GHS07 GHS08

· Signal word Danger

Hazard-determining

components of labelling: diphenylmethanediisocyanate,isomeres and homologues

diphenylmethane-4,4'-di-isocyanante Diphenylmethane-2,4'-diisocyanate diphenylmethane-2,2'-diisocyanate

· Hazard statements H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated

exposure.

• Precautionary statements P260 Do not breathe dust/fume/gas/mist/vapours/

spray.

P280 Wear protective gloves/protective clothing/eye

protection/face protection/hearing protection.

P284 [In case of inadequate ventilation] wear

respiratory protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P342+P311 If experiencing respiratory symptoms: Call a

POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container

tightly closed.

• Additional information: EUH401 To avoid risks to human health and the environment,

comply with the instructions for use.

EUH204 Contains isocyanates. May produce an allergic reaction. As from 24 August 2023 adequate training is required before

industrial or professional use.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

GB



Page 3/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

Trade name MC-Flex 2098 - Komponente B

(Contd. of page 2)

3.2 Mixtures Description:	Mixture consisting of the following components.	
Dangerous components:		
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5$ % Skin Irrit. 2; H315: $C \ge 5$ % Resp. Sens. 1; H334: $C \ge 0.1$ % STOT SE 3; H335: $C \ge 5$ %	60-809
CAS: 101-68-8 EINECS: 202-966-0 Reg.nr.: 01-2119457014-47	diphenylmethane-4,4'-di-isocyanante Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5$ % Skin Irrit. 2; H315: $C \ge 5$ % Resp. Sens. 1; H334: $C \ge 0.1$ % STOT SE 3; H335: $C \ge 5$ %	10-30
CAS: 5873-54-1 EINECS: 227-534-9	Diphenylmethane-2,4'-diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5$ % Skin Irrit. 2; H315: $C \ge 5$ % Resp. Sens. 1; H334: $C \ge 0.1$ % STOT SE 3; H335: $C \ge 5$ %	≥5-<10
CAS: 2536-05-2 EINECS: 219-799-4	diphenylmethane-2,2'-diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5$ % Skin Irrit. 2; H315: $C \ge 5$ % Resp. Sens. 1; H334: $C \ge 0.1$ % STOT SE 3; H335: $C \ge 5$ %	<0.19



Page 4/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

Trade name MC-Flex 2098 - Komponente B

(Contd. of page 3)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information Remove, decontaminate and dispose of soiled, soaked clothing

and shoes immediately.

· After inhalation Remove person to fresh air, keep warm, allow to rest; if breathing

is difficult, seek medical attention.

· After skin contact In case of contact with skin, preferably wash with polyethylene

glycol-based cleaner or clean with plenty of warm water and soap.

Consult a doctor in case of skin reactions.

· After eye contact Rinse the eyes with open eyelids for a sufficiently long time (at

least 10 minutes) with water that is as lukewarm as possible.

Consult an ophthalmologist.

· After swallowing Do NOT induce vomiting. Rinse mouth with water. Medical

attention required.

· 4.2 Most important symptoms and effects, both acute and

delayed Information for the doctor: The product irritates the respiratory tract

and is a potential trigger for skin and respiratory sensitisation. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Depending on the extent of exposure and the

symptoms, prolonged medical treatment may be necessary.

· 4.3 Indication of any immediate medical attention

and special treatment needed No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or

mixture No further relevant information available.

· 5.3 Advice for firefighters

· **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: No special measures required.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

(Contd. on page 5)



Page 5/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

Ensure adequate ventilation.

Trade name MC-Flex 2098 - Komponente B

(Contd. of page 4)

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure sufficient air exchange and/or extraction in the work areas.

Air extraction is required for spray application.

For solid products: Avoid dust formation and dust deposits. Air limit values mentioned in section 8 must be monitored.

At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being

exceeded. The air must be moved away from people.

For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.

· 7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance

reasons can be found in our technical data sheet.

· Storage

Requirements to be met by

storerooms and containers: Store only in the original container.

· Further information about

storage conditions: None.
Storage class 10

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m³

Long-term value: 0.02 mg/m³

Sen; as -NCO

(Contd. on page 6)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

Trade name MC-Flex 2098 - Komponente B

CAS	101-68-8 diphenylmethane-4,4'-di-isocyanante	(Contd. of pa
	Short-term value: 0.07 mg/m³	
	Long-term value: 0.02 mg/m³	
040	Sen; as -NCO	
	5873-54-1 Diphenylmethane-2,4'-diisocyanate Short-term value: 0.07 mg/m³	
VVEL	Long-term value: 0.02 mg/m³	
	Sen; as -NCO	
CAS	2536-05-2 diphenylmethane-2,2'-diisocyanate	
WEL	Short-term value: 0.07 mg/m³	
	Long-term value: 0.02 mg/m³ Sen; as -NCO	
· DNE		
	9016-87-9 diphenylmethanediisocyanate,isomeres and homologues	
	ative DNEL 0.05 mg/m³ (ArL)	
	101-68-8 diphenylmethane-4,4'-di-isocyanante	
Derm		
	ative DNEL 0.05 mg/m³ (ArL)	
	5873-54-1 Diphenylmethane-2,4'-diisocyanate	
	ative DNEL 0.05 mg/m³ (ArL)	
· PNE	Os	
CAS	9016-87-9 diphenylmethanediisocyanate,isomeres and homologues	
PNE	1 mg/l (Sewage Treatment Plant)	
	0.1 mg/l (Mew)	
	1 mg/l (Freshwater)	
PNE	1 mg/kg dwt (Bod)	
	101-68-8 diphenylmethane-4,4'-di-isocyanante	
PNE	1 mg/l (Sewage Treatment Plant)	
	0.1 mg/l (Mew)	
	1 mg/l (Freshwater)	
	1 mg/kg dwt (Bod)	
	5873-54-1 Diphenylmethane-2,4'-diisocyanate	
PNE	C 1 mg/l (Sewage Treatment Plant)	
	0.1 mg/l (Mew) 1 mg/l (Freshwater)	
PNE		
_	dients with biological limit values: 101-68-8 diphenylmethane-4,4'-di-isocyanante	
BMG		
טויום	Medium: urine	
	Sampling time: At the end of the period od exposure	

(Contd. on page 7)



Page 7/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

Trade name MC-Flex 2098 - Komponente B

(Contd. of page 6)

CAS: 5873-54-1 Diphenylmethane-2,4'-diisocyanate

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

CAS: 2536-05-2 diphenylmethane-2,2'-diisocyanate

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

• Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

· Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

Breathing equipment: Respiratory protection required at insufficiently ventilated

workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-

term work.

If applicable, further recommendations for respiratory protection

can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic

bronchitis), handling of the product is not recommended.

Hand protection Suitable materials for protective gloves; EN 374:

Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).

Note: suitable materials that provide sufficient protection for industrial cleaning with aprotic polar solvents (according to IUPAC

definition): butyl rubber.

In case of prolonged or frequently repeated contact, a glove with a protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN374). For short-term contact, a glove with a protection class of 3 or higher is recommended (breakthrough time greater than 60 minutes

according to EN374).

The thickness of the material is not the only criterion for the level of protection of a glove against a chemical substance. The protective effect also depends to a large extent on the type of glove material. Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multilayer gloves, which guarantee sufficient protection even with a thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide

(Contd. on page 8)



Page 8/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 01.03.2024 Printing date 01.03.2024 Version number 30 (replaces version 29)

Trade name MC-Flex 2098 - Komponente B

(Contd. of page 7)

sufficient protection for short periods of wear.

For solvent-free products:

Example:

Polychloroprene - CR: thickness ≥0.5mm; breakthrough time

≥480min.

Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time

Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time

≥480min.

Recommendation: Dispose of contaminated gloves.

· Material of gloves Polychloroprene - CR

Nitrile rubber - NBR Butyl rubber - IIR Fluoro rubber - FKM

Penetration time of glove

material Polychloroprene - CR: thickness ≥0.5mm; breakthrough time

>480min.

Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time

>480min.

Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: Thickness ≥0.4mm; Breakthrough time

≥480min.

· Eye/face protection

Safety goggles with side protection in accordance with EN 166. Use chemical-resistant protective clothing.

· Body protection:

In case of hypersensitivity of the skin, handling the product is not

recommended.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Whitish · Smell: Characteristic Melting point/freezing point: Not determined

Boiling point or initial boiling point and

° C boiling range (CAS: 9016-87-9 190

diphenylmethanediisocyanate, isomeres and

homologues) >200 °C

· Flash point: · pH Not applicable. Not determined.

· Viscosity:

Not determined. · Kinematic viscosity · dynamic at 20 °C: 145 mPas

(Contd. on page 9)



Page 9/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

Trade name MC-Flex 2098 - Komponente B

(Contd. of page 8)

· Solubility

· Water: Not miscible or difficult to mix

• Steam pressure at 25 °C: 0 h P a (CAS: 9016-87-9

diphenylmethanediisocyanate, isomeres and

homologues)

· Density and/or relative density

Density at 20 °C 1.19 g/cm³

· 9.2 Other information

· Appearance:

Form: Fluid

Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

Information with regard to physical hazard

classes

· Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit

flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions Reacts with amines

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 10)



Page 10/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

Trade name MC-Flex 2098 - Komponente B

(Contd. of page 9)

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Harmful if inhaled.

· LD/LC50 values that are relevant for classification:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

 Oral
 LD50
 >10000 mg/kg (Rat)

 Dermal
 LD50
 >5000 mg/kg (Rab)

 Inhalative
 LC50/4 h
 ~450 mg/l (Rat)

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanante

 Oral
 LD50
 >10000 mg/kg (rat)

 Dermal
 LD50
 >9400 mg/kg (rabbit)

Skin corrosion/irritation
 Serious eye damage/irritation
 Causes skin irritation.
 Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

May cause an allergic skin reaction.

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Suspected of causing cancer.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure May cause respiratory irritation.

STOT-repeated exposure May cause damage to organs through prolonged or repeated

exposure.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanante

EC50/24h >1000 mg/l (Daphnia magna) LC50/96h >1000 mg/l (Brachydanio rerio) NOEC >1000 mg/l (Eisenia foetida)

>10 mg/l (Daphnia magna)

(Contd. on page 11)



Page 11/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

Trade name MC-Flex 2098 - Komponente B

(Contd. of page 10)

· 12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void	
	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accordi	ng to	
IMO instruments	Not applicable.	

(Contd. on page 12)



Page 12/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

Trade name MC-Flex 2098 - Komponente B

(Contd. of page 11)

UN "Model Regulation":

Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture

No further relevant information available.

- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases	U215	Causes skin irritation.
Relevant prirases	H315	Causes skiri irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or

repeated exposure.

EUH204 Contains isocyanates. May produce an allergic reaction.

· Department issuing data

specification sheet:

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 13)



Page 13/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024 Version number 30 (replaces version 29) Revision: 01.03.2024

Trade name MC-Flex 2098 - Komponente B

(Contd. of page 12)

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

- GB

^{*} Data compared to the previous version altered.