



BE SURE. BUILD SURE.

Page 1/14

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **MC-Flex 2099 - Komponente B**

Article number: 1004

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Application of the substance / the mixture

Polyurethane resin  
Hardening agent/ Curing agent

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

#### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)  
Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

#### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 1)

**· Hazard pictograms**



GHS07 GHS08

**· Signal word**

*Danger*

**· Hazard-determining components of labelling:**

*diphenylmethanediisocyanate, isomeres and homologues  
diphenylmethane-4,4'-di-isocyanate  
Diphenylmethane-2,4'-diisocyanate  
MDI-based polyisocyanate prepolymer  
diphenylmethane-2,2'-diisocyanate*

**· Hazard statements**

*H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.*

**· Precautionary statements**

*P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P284 [In case of inadequate ventilation] wear respiratory protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.*

**· Additional information:**

*EUH401 To avoid risks to human health and the environment, comply with the instructions for use.  
EUH204 Contains isocyanates. May produce an allergic reaction.  
As from 24 August 2023 adequate training is required before industrial or professional use.*

**· 2.3 Other hazards**

**· Results of PBT and vPvB assessment**

- PBT:** *Not applicable.*
- vPvB:** *Not applicable.*

GB

(Contd. on page 3)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 2)

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Description:**

Active substance with propellant.

Mixture consisting of the following components.

**Dangerous components:**

CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	30-60%
CAS: 101-68-8 EINECS: 202-966-0 Reg.nr.: 01-2119457014-47	diphenylmethane-4,4'-di-isocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	10-30%
CAS: 5873-54-1 EINECS: 227-534-9	Diphenylmethane-2,4'-diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	10-30%
CAS: 67815-87-6	MDI-based polyisocyanate prepolymer Resp. Sens. 1, H334; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥10-<20%

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Page 4/14

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

Trade name **MC-Flex 2099 - Komponente B**

(Contd. of page 3)

CAS: 2536-05-2 EINECS: 219-799-4	diphenylmethane-2,2'-diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	≥1-<2.5%
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	≥1-<2.5%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

- **General information** Remove, decontaminate and dispose of soiled, soaked clothing and shoes immediately.
- **After inhalation** Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.
- **After skin contact** In case of contact with skin, preferably wash with polyethylene glycol-based cleaner or clean with plenty of warm water and soap. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.
- **After swallowing** Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

#### · 4.2 Most important symptoms and effects, both acute and delayed

Information for the doctor: The product irritates the respiratory tract and is a potential trigger for skin and respiratory sensitisation. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Depending on the extent of exposure and the symptoms, prolonged medical treatment may be necessary.

- **4.3 Indication of any immediate medical attention and special treatment needed** No information available.

GB

(Contd. on page 5)



BE SURE. BUILD SURE.

Page 5/14

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

Trade name MC-Flex 2099 - Komponente B

(Contd. of page 4)

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture**
  - Can be released in case of fire
  - Carbon monoxide (CO)
  - Nitrogen oxides (NO<sub>x</sub>)
  - Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
  - Hydrogen cyanide (HCN)
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained breathing apparatus.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
  - Ensure adequate ventilation
  - Use breathing protection against the effects of fumes/dust/aerosol.
- **6.2 Environmental precautions:** Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose of contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**
  - See Section 7 for information on safe handling
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for information on disposal.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
  - Ensure sufficient air exchange and/or extraction in the work areas.
  - Air extraction is required for spray application.
  - For solid products: Avoid dust formation and dust deposits.
  - Air limit values mentioned in section 8 must be monitored.
  - At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.
  - For products containing solvents: Explosion protection required.
  - The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes

(Contd. on page 6)

GB



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 5)

and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.

**· 7.2 Conditions for safe storage, including any incompatibilities**

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

**· Storage**

**· Requirements to be met by storerooms and containers:**

Store only in the original container.

**· Information about storage in one common storage facility:**

Store away from foodstuffs.

**· Further information about storage conditions:**

None.

**· Storage class**

10

**· 7.3 Specific end use(s)**

No further relevant information available.

### SECTION 8: Exposure controls/personal protection

**· 8.1 Control parameters**

**· Components with critical values that require monitoring at the workplace:**

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

WEL Short-term value: 0.07 mg/m<sup>3</sup>  
Long-term value: 0.02 mg/m<sup>3</sup>  
Sen; as -NCO

**CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate**

WEL Short-term value: 0.07 mg/m<sup>3</sup>  
Long-term value: 0.02 mg/m<sup>3</sup>  
Sen; as -NCO

**CAS: 5873-54-1 Diphenylmethane-2,4'-diisocyanate**

WEL Short-term value: 0.07 mg/m<sup>3</sup>  
Long-term value: 0.02 mg/m<sup>3</sup>  
Sen; as -NCO

**CAS: 2536-05-2 diphenylmethane-2,2'-diisocyanate**

WEL Short-term value: 0.07 mg/m<sup>3</sup>  
Long-term value: 0.02 mg/m<sup>3</sup>  
Sen; as -NCO

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

WEL Short-term value: 0.07 mg/m<sup>3</sup>  
Long-term value: 0.02 mg/m<sup>3</sup>  
Sen; as -NCO

(Contd. on page 7)



BE SURE. BUILD SURE.

**Safety data sheet**  
according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 6)

**· DNELs**

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Inhalative DNEL 0.05 mg/m<sup>3</sup> (ArL)

**CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate**

Dermal DNEL 50 mg/kg bw/day (Ark)

Inhalative DNEL 0.05 mg/m<sup>3</sup> (ArL)

**CAS: 5873-54-1 Diphenylmethane-2,4'-diisocyanate**

Inhalative DNEL 0.05 mg/m<sup>3</sup> (ArL)

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Inhalative DNEL 0.05 mg/m<sup>3</sup> (ArL)

**· PNECs**

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

PNEC 1 mg/l (Sewage Treatment Plant)

0.1 mg/l (Mew)

1 mg/l (Freshwater)

PNEC 1 mg/kg dwt (Bod)

**CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate**

PNEC 1 mg/l (Sewage Treatment Plant)

0.1 mg/l (Mew)

1 mg/l (Freshwater)

PNEC 1 mg/kg dwt (Bod)

**CAS: 5873-54-1 Diphenylmethane-2,4'-diisocyanate**

PNEC 1 mg/l (Sewage Treatment Plant)

0.1 mg/l (Mew)

1 mg/l (Freshwater)

PNEC 1 mg/kg dwt (Bod)

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

PNEC 1 mg/l (Sewage Treatment Plant)

0.1 mg/l (Mew)

1 mg/l (Freshwater)

PNEC 1 mg/kg dwt (Bod)

**· Ingredients with biological limit values:**

**CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate**

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period of exposure

Parameter: isocyanate-derived diamine

(Contd. on page 8)



BE SURE. BUILD SURE.

Page 8/14

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

Trade name MC-Flex 2099 - Komponente B

(Contd. of page 7)

### CAS: 5873-54-1 Diphenylmethane-2,4'-diisocyanate

BMGV 1 µmol creatinine/mol  
Medium: urine  
Sampling time: At the end of the period of exposure  
Parameter: isocyanate-derived diamine

### CAS: 2536-05-2 diphenylmethane-2,2'-diisocyanate

BMGV 1 µmol creatinine/mol  
Medium: urine  
Sampling time: At the end of the period of exposure  
Parameter: isocyanate-derived diamine

- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**

Keep away from food, drink and animal feed.  
Remove soiled, soaked clothing immediately.  
Wash hands before breaks and at the end of work.  
Avoid contact with eyes and skin.
- **Breathing equipment:** Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.  
If applicable, further recommendations for respiratory protection can be found in the appendix.  
In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.
- **Hand protection** Suitable materials for protective gloves; EN 374:  
Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).  
Note: suitable materials that provide sufficient protection for industrial cleaning with aprotic polar solvents (according to IUPAC definition): butyl rubber.  
In case of prolonged or frequently repeated contact, a glove with a protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN374). For short-term contact, a glove with a protection class of 3 or higher is recommended (breakthrough time greater than 60 minutes according to EN374).  
The thickness of the material is not the only criterion for the level of protection of a glove against a chemical substance. The protective effect also depends to a large extent on the type of glove material. Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multi-layer gloves, which guarantee sufficient protection even with a thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide

(Contd. on page 9)

GB





BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 8)

sufficient protection for short periods of wear.

For solvent-free products:

Example:

Polychloroprene - CR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Nitrile rubber - NBR: thickness  $\geq 0.35\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Butyl rubber - IIR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Fluoro rubber - FKM: thickness  $\geq 0.4\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Recommendation: Dispose of contaminated gloves.

· **Material of gloves**

Polychloroprene - CR

Nitrile rubber - NBR

Butyl rubber - IIR

Fluoro rubber - FKM

· **Penetration time of glove material**

Polychloroprene - CR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Nitrile rubber - NBR: thickness  $\geq 0.35\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Butyl rubber - IIR: thickness  $\geq 0.5\text{mm}$ ; breakthrough time  $\geq 480\text{min}$ .

Fluoro rubber - FKM: Thickness  $\geq 0.4\text{mm}$ ; Breakthrough time  $\geq 480\text{min}$ .

· **Eye/face protection**

Safety goggles with side protection in accordance with EN 166.

· **Body protection:**

Use chemical-resistant protective clothing.

In case of hypersensitivity of the skin, handling the product is not recommended.

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

· **Colour:**

Dark brown

· **Smell:**

Characteristic

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

190 °C (CAS: 9016-87-9  
diphenylmethanediisocyanate, isomeres and homologues)

· **Flash point:**

201 °C

· **Auto-ignition temperature:**

400 °C (CAS: 9016-87-9  
diphenylmethanediisocyanate, isomeres and homologues)

· **pH**

Not applicable.

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

(Contd. on page 10)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 9)

· <b>dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>Water:</b>	Hydrolyzed
· <b>Steam pressure at 25 °C:</b>	0 hPa (CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues)
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C</b>	1.19 g/cm <sup>3</sup>

**9.2 Other information**

· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive.

**Information with regard to physical hazard classes**

· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

· <b>10.1 Reactivity</b>	No further relevant information available.
· <b>10.2 Chemical stability</b>	
· <b>Thermal decomposition / conditions to be avoided:</b>	No decomposition if used according to specifications.
· <b>10.3 Possibility of hazardous reactions</b>	Reacts with amines
· <b>10.4 Conditions to avoid</b>	No further relevant information available.
· <b>10.5 Incompatible materials:</b>	No further relevant information available.

(Contd. on page 11)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

Trade name MC-Flex 2099 - Komponente B

(Contd. of page 10)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

#### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

- **LD/LC50 values that are relevant for classification:**

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Oral LD50 >10000 mg/kg (Rat)

Dermal LD50 >5000 mg/kg (Rab)

Inhalative LC50/4 h ~450 mg/l (Rat)

**CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate**

Oral LD50 >10000 mg/kg (rat)

Dermal LD50 >9400 mg/kg (rabbit)

**CAS: 2536-05-2 diphenylmethane-2,2'-diisocyanate**

Inhalative LC50/4 h 0.527 mg/l (rat)

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

Oral LD50 >10000 mg/kg (Rat)

Dermal LD50 >5000 mg/kg (Rab)

Inhalative LC50/4 h ~450 mg/l (Rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

GB

(Contd. on page 12)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

Trade name MC-Flex 2099 - Komponente B

(Contd. of page 11)

#### SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 101-68-8 diphenylmethane-4,4'-di-isocyanate

EC50/24h >1000 mg/l (Daphnia magna)

LC50/96h >1000 mg/l (Brachydanio rerio)

NOEC >1000 mg/l (Eisenia foetida)

>10 mg/l (Daphnia magna)

· 12.2 Persistence and degradability

No further relevant information available.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· PBT:

Not applicable.

· vPvB:

Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

#### SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

#### SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA

Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA

Void

(Contd. on page 13)



BE SURE. BUILD SURE.

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 12)

· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR, ADN, IMDG, IATA</b>	
· <b>Class</b>	Void
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b>	Not applicable.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>UN "Model Regulation":</b>	Void

#### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture** No further relevant information available.

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· <b>Relevant phrases</b>	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H332	Harmful if inhaled.
	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 14)



BE SURE. BUILD SURE.

Page 14/14

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 40 (replaces version 39)

Revision: 01.03.2024

**Trade name MC-Flex 2099 - Komponente B**

(Contd. of page 13)

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH204 Contains isocyanates. May produce an allergic reaction.

· **Department issuing data specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· **\* Data compared to the previous version altered.**

GB