

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **Mycoflex 4100 TS - Komponente A**

Article number: 966

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Primer/ Subcoating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word**

Warning

· **Hazard-determining components of labelling:**

Reaction mass of ethylbenzene and xylene epoxide derivates
1-methoxypropan-2-ol

· **Hazard statements**

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

H412 Harmful to aquatic life with long lasting effects.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

· **Additional information:**

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture consisting of the following components.

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 2)

· Dangerous components:

EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34	Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	30-60%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-methoxypropan-2-ol Flam. Liq. 3, H226; STOT SE 3, H336	30-60%
CAS: 1675-54-3 EINECS: 216-823-5	epoxide derivates Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	≥10-<25%
CAS: 2530-83-8 EINECS: 219-784-2	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318	≥1-<1.5%
CAS: 1589-47-5 EINECS: 216-455-5	2-methoxypropanol Flam. Liq. 3, H226; Repr. 1B, H360D; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	<0.3%

· Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Immediately remove any clothing contaminated with the product.
Take affected persons into the open air.

· After inhalation

Supply fresh air and call for doctor for safety reasons.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

· After eye contact

Rinse opened eye for several minutes under running water.
Seek medical treatment.

· After swallowing

Do not induce vomiting; instantly call for medical help.

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· For safety reasons unsuitable extinguishing agents

Water with a full water jet.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 3)

· **5.3 Advice for firefighters**

· **Protective equipment:** Put on breathing apparatus.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Prevent material from reaching sewage system, holes and cellars.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Store in cool, dry place in tightly closed containers.

Open and handle container with care.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:**

No special requirements.

· **Information about storage in one common storage facility:**

Not required.

· **Further information about storage conditions:**

Keep container tightly sealed.

· **Storage class**

3

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

CAS: 107-98-2 1-methoxypropan-2-ol

WEL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

Sk

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 4)

· DNELs

Reaction mass of ethylbenzene and xylene

Oral	DNEL	1.6 mg/kg bw/Tag (ArL) mg/kg bw/Tag (Workers)
Dermal	DNEL	180 mg/kg bw/day (ArL)
Inhalative	DNEL	211 mg/m ³ (ArL)

CAS: 107-98-2 1-methoxypropan-2-ol

Oral	DNEL	3.3 mg/kg bw/Tag (ArL)
Dermal	DNEL	50.6 mg/kg bw/day (ArL)
Inhalative	DNEL	369 mg/m ³ (ArL)

· CAS No. Designation of material % Type Value Unit

· Additional Occupational Exposure Limit Values for possible hazards during processing:

CAS: 1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

CAS: 100-41-4 Ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
-----	---

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Avoid contact with the eyes and skin.

· Breathing equipment:

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· Hand protection

Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

After use of gloves apply skin-cleaning agents and skin cosmetics.
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 5)

calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.

· **Eye/face protection**

Not required.

· **Body protection:**

Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· **Colour:**

Yellow

· **Smell:**

Characteristic

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

120.3 °C (CAS: 107-98-2 1-methoxypropan-2-ol)

· **Lower and upper explosion limit**

· **Lower:**

1 Vol % (Reaction mass of ethylbenzene and xylene)

· **Upper:**

13.7 Vol % (CAS: 107-98-2 1-methoxypropan-2-ol)

· **Flash point:**

25 °C

· **Auto-ignition temperature:**

184 °C (CAS: 25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues molecular weight < 700)

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity at 20 °C**

22 s (DIN 53211/4)

· **dynamic:**

Not determined.

· **Solubility**

· **Water:**

Not miscible or difficult to mix

· **Steam pressure at 20 °C:**

13 hPa (CAS: 107-98-2 1-methoxypropan-2-ol)

· **Vapour pressure at 50 °C:**

45 hPa

· **Density and/or relative density**

· **Density at 20 °C**

0.94 g/cm³

· 9.2 Other information

· **Appearance:**

· **Form:**

Fluid

· **Important information on protection of health and environment, and on safety.**

· **Self-inflammability:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/steam mixtures is possible.

(Contd. on page 7)

GB

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 6)

Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.
· 10.6 Hazardous decomposition products:	No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008	
· Acute toxicity	Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

Reaction mass of ethylbenzene and xylene

Oral	LD50	3523-4000 mg/kg (rat)
Dermal	LD50	1100 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (rat)

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 7)

CAS: 107-98-2 1-methoxypropan-2-ol

Oral	LD50	4016 mg/kg (rat)
Dermal	LD50	13000 mg/kg (rabbit)
Inhalative	LC50/4 h	54.6 mg/l (rat)

CAS: 1675-54-3 epoxide derivatives

Dermal	LD50	23000 mg/kg (rabbit)
--------	------	----------------------

CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Oral	LD50	8030 mg/kg (rat)
Dermal	LD50	4248 mg/kg (rabbit)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclotetrasiloxane	List II
CAS: 556-67-2	octamethylcyclotetrasiloxane	List II; III

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

Reaction mass of ethylbenzene and xylene

EC50/72h	2.2 mg/l (Selenastrum capricornutum)
LC50/96h	2.6 mg/l (Oncorhynchus mykiss)
NOEC	16 mg/l (BEL)

CAS: 107-98-2 1-methoxypropan-2-ol

IC50	1000 mg/l (BEL)
LC50/96h	6812 mg/l (Leucidus idus)
LC50/48h	23300 mg/l (Daphnia magna)
EC50/48h	23300 mg/l (Daphnia magna)

CAS: 1675-54-3 epoxide derivatives

IC50	>42.6 mg/l (Bak)
------	------------------

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 8)

LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)

CAS: 2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

LC50/96h	55 mg/l (Cyp)
EC50/48h	473 mg/l (Daphnia magna)
ErC50/72h	255 mg/l (Scenedesmus subspicatus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

SECTION 14: Transport information

- | | |
|--|---------------------------|
| · 14.1 UN number or ID number | |
| · ADR, IMDG, IATA | UN1866 |
| · 14.2 UN proper shipping name | |
| · ADR, IMDG, IATA | RESIN SOLUTION |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
| · Class | 3 (F1) Flammable liquids. |
| · Label | 3 |

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 9)

· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Kemler Number:	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· Remarks:	Beförderung nach RN 2301a
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

(Contd. on page 11)



BE SURE. BUILD SURE.

Page 11/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 10)

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Qualifying quantity (tonnes)
for the application of lower-
tier requirements**

5000 t

· **Qualifying quantity (tonnes)
for the application of upper-
tier requirements**

50000 t

· **15.2 Chemical safety
assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360D May damage the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **Department issuing data
specification sheet:**

Environment protection department.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

(Contd. on page 12)

GB

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024

Version number 33 (replaces version 32)

Revision: 09.03.2024

Trade name Mycoflex 4100 TS - Komponente A

(Contd. of page 11)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the
previous version altered.**