

Page 1/9

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2024 Version number 38 (replaces version 37) Revision: 15.03.2024

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name Nafufill KM 250 HS

794 · Article number:

· 1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Concrete surfacer

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

1.4 Emergency telephone

number:

msds@mc-bauchemie.de

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07

Danger

· Signal word

(Contd. on page 2)



Page 2/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2024 Version number 38 (replaces version 37) Revision: 15.03.2024

#### Trade name Nafufill KM 250 HS

(Contd. of page 1)

Hazard-determining

components of labelling: Portland cement

Burnt oil shale

P362+P364

Fly ash Portland cement

• Hazard statements H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

• Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/

spray.

spray.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

Take off contaminated clothing and wash it

before reuse.
P403+P233 Store in a well-ventilated place. Keep container

tightly closed.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:		
CAS: 65997-15-1 EINECS: 266-043-4	Portland cement Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥20-≤30%
CAS: 93685-99-5 Reg.nr.: 01-2119703178-42- 0000	Burnt oil shale STOT RE 2, H373; Eye Dam. 1, H318; STOT SE 3, H335	≥3-<10%
CAS: 68475-76-3	Fly ash Portland cement Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥1-<1.5%
· Additional information	For the wording of the listed hazard phrases refer to s	action 16

• Additional information For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

· After inhalation Supply fresh air.

In case of unconsciousness bring patient into stable side position

for transport.

· After skin contact Instantly wash with water and soap and rinse thoroughly.

(Contd. on page 3)



Page 3/9

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 15.03.2024 Printing date 15.03.2024 Version number 38 (replaces version 37)

#### Trade name Nafufill KM 250 HS

(Contd. of page 2)

· After eye contact Rinse opened eye for several minutes under running water.

Seek medical treatment.

· After swallowing Rinse out mouth and then drink plenty of water.

Seek medical treatment.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

· Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with

water jet or alcohol-resistant foam.

· 5.2 Special hazards arising

from the substance or mixture

No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions:

No special measures required. · 6.3 Methods and material for

containment and cleaning up: Collect mechanically.

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe

handling Prevent formation of dust.

· Information about protection

against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Information about storage in

one common storage facility: Not required.

· Further information about

storage conditions: None.

(Contd. on page 4)



Page 4/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2024 Version number 38 (replaces version 37) Revision: 15.03.2024

Trade name Nafufill KM 250 HS

(Contd. of page 3)

· Storage class

13

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 65997-15-1 Portland cement

WEL Long-term value: 10\* 4\*\* mg/m³
\*inhalable dust \*\*respirable dust

minalable dast respirable

·DNELs

CAS: 65997-15-1 Portland cement

Inhalative DNEL 1 mg/m³ (ArL)

CAS: 93685-99-5 Burnt oil shale

Inhalative DNEL 0.233 mg/m³ (ArL)

· PNECs

CAS: 93685-99-5 Burnt oil shale

PNEC 100 mg/l (BEL)

0.002 mg/l (Mew)

0.02 mg/l (Freshwater)

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and

hygienic measures Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment: Wear respiratory protection in case of insufficient ventilation.

The selection of respirators (EN 14387) must be based on the known or anticipated exposure concentrations, the hazards of the product and the occupational exposure limits (section 8.1) of the

respirator in question.

Particle filter PP1: Inert substance; P2, P3: Hazardous substances Provide adequate ventilation. This can be achieved by local

exhaust ventilation or general exhaust ventilation. (EN 689 - Methods for determining inhalation exposure) This applies especially at the mixing or stirring place.

If this is not sufficient to keep the concentration below the

occupational exposure limit, provide respiratory protection.

· Hand protection Protective gloves.

(Contd. on page 5)



Page 5/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2024 Version number 38 (replaces version 37) Revision: 15.03.2024

#### Trade name Nafufill KM 250 HS

(Contd. of page 4)

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

Strong gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

application.

· Penetration time of glove

material

The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

· Eye/face protection

Not required.

Body protection:

· Material of gloves

Protective work clothing.

#### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: Whitish
 Smell: Odourless
 Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range 2230 °C (CAS: 14808-60-7 Quartz (SiO2))

· Flash point: Not applicable

pH at 20 °C 11

· Viscosity:

Kinematic viscositydynamic:Not applicable.Not applicable.

· Solubility

· Water: Unsoluble

• Steam pressure at 1732 °C: 13.5 hPa (CAS: 14808-60-7 Quartz (SiO2))

Density and/or relative density

Density at 20 °C 2.74 g/cm³

· 9.2 Other information

· Appearance:

· Form: Powder

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void

(Contd. on page 6)



Page 6/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2024 Version number 38 (replaces version 37) Revision: 15.03.2024

#### Trade name Nafufill KM 250 HS

(Contd. of page 5)

· Aerosols	Void
· Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
Corrosive to metals	Void
· Desensitised explosives	Void

## **SECTION 10: Stability and reactivity**

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

**conditions to be avoided:** No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

## **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:					
I	CAS: 659	97-15-1 Po	ortland cement		
	Dermal	LD50	2000 mg/kg (rabbit)		
	Inhalative	LC50/4 h	5 mg/l (rat)		
	CAS: 93685-99-5 Burnt oil shale				
Ī	Oral	LD50	>2000 mg/kg (rat)		
١	Inhalative	LOAEL	0.000699 mg/l (ArL)		

Skin corrosion/irritation
 Serious eye damage/irritation
 Causes skin irritation.
 Causes serious eye damage.

• Germ cell mutagenicity
• Carcinogenicity

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

(Contd. on page 7)



Page 7/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2024 Version number 38 (replaces version 37) Revision: 15.03.2024

#### Trade name Nafufill KM 250 HS

(Contd. of page 6)

• Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure May cause respiratory irritation.

• STOT-repeated exposure
• Aspiration hazard

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

CAS: 128-37-0 2,6-Di-tert-butyl-p-cresol

List II

#### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 93685-99-5 Burnt oil shale

EC50/72h 82.7 mg/l (Selenastrum capricornutum)

LC50/96h >100 mg/l (fish)

EC50/48h >100 mg/l (Daphnia magna)

NOEC >100 mg/l (fish)

· 12.2 Persistence and

**degradability** No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.
12.4 Mobility in soil
No further relevant information available.

• 12.5 Results of PBT and vPvB assessment
• PBT:
• vPvB:
Not applicable.
Not applicable.

· 12.6 Endocrine disrupting

properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

#### SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Non contaminated packagings can be used for recycling.

GB



Page 8/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2024 Version number 38 (replaces version 37) Revision: 15.03.2024

Trade name Nafufill KM 250 HS

(Contd. of page 7)

14.1 UN number or ID number	
ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name	
ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according	ng to
IMO instruments	Not applicable.

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

CAS: 1310-58-3 potassium hydroxide

17% of total caustic alkalinity

15.2 Chemical safety

assessment:

A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)



Page 9/9

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 15.03.2024 Printing date 15.03.2024 Version number 38 (replaces version 37)

#### Trade name Nafufill KM 250 HS

(Contd. of page 8)

· Relevant phrases H315 Causes skin irritation.

> H318 Causes serious eve damage. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated

exposure.

· Department issuing data

specification sheet:

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

\* \* Data compared to the previous version altered.