

MC-Estribond T 15

Primer for cement-bound substrates



PRODUCT PROPERTIES

- Liquid
- Single-component
- Solvent free
- Reduces absorbency
- Stabilizing effect
- Can be sprayed and rolled

AREAS OF APPLICATION

- Primer for absorbent substrates underneath MC-Floor Easyplan classic und MC-Floor Screed classic
- Primer for absorbent substrates underneath Concrete Cosmetics
- Slight stabilization of dusting and sanding substrates
- Deep primer for highly absorbent substrates

APPLICATION ADVICE

Substrate Preparation

The substrate must be clean, dry, load-bearing and free of all loose particles, dust, oil and other separating substances. Existing coatings must be removed. When used as primer underneath MC-Floor Easyplan classic und MC-Floor Screed classic, it is recommended to thoroughly pre-wet mineral substrates. Puddle-formation should be avoided.

Application

MC-Estribond T 15 is ready to use and is applied undiluted with brush or roller. Apply only small amounts to avoid the formation of a shiny, adhesion-reducing surface-film. Puddle-formation should be avoided under any circumstances. Highly absorbent substrates should be primed twice.

Depending on the absorbency and rough-ness of the substrate, approx. 150 - 250 ml/m² of MC-Estribond T 15 is required. Deviations from this average can be determined in object-related preliminary tests.

MC-Floor Easyplan classic und MC-Floor Screed classic can be applied as soon as the primer is completely dry. Longer waiting periods before the application of the subsequent coatings can lead to adhesion-reducing contaminations and should therefore be avoided.

Further Information

Consumption, processing time and all technical properties depend very much on the temperatures and the object conditions.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

| Characteristic | Unit | Value | Comments |
|--------------------|-------------------|-------------------|--|
| Consumption | ml/m ² | approx. 150 - 250 | depending on substrate and application |
| Overworkable after | hours | approx. 1 | |
| Density | g/cm ³ | approx. 1.02 | |

All technical values are laboratory results determined at 21°C ±2°C and 50% relative humidity.

| | |
|--------------------------|---|
| Base | plastic dispersion |
| Form | liquid |
| Equipment cleaning agent | water |
| Colour | milky white |
| Delivery form | 10 l canister |
| Self-monitoring | EN ISO 9001 |
| Storage | Can be stored in cool and dry conditions for at least 12 months in original unopened packs. |
| Packaging disposal | Make sure single-use containers are completely empty. |

Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets.

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2300018517]