

MC-Montan Drive DF

Defoamer



PRODUCT PROPERTIES

- Removing the foam
- Reduction of foam formation

AREAS OF APPLICATION

- Cleaning of foam-treated surfaces
- Defoamers for foam-conditioned soils

APPLICATION ADVICE

MC-Montan Drive DF changes the surface tension of foams produced by the use of foam concentrates. As a result, the foam loses its stability and collapses.

MC-Montan Drive DF need to be diluted in water as a working solution with a ratio of 1:9.

The "MC-Business Unit Tunnelling" is available for individual recommendation and optimization of the application on site.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Density	kg/dm ³	0.92 - 0.96	
Water pollution hazard class		WGK 1	
Designation of admixture		MC-Montan Drive DF	
Colour		yellowish	
Form		liquid	
In-company production control		EN ISO 9001	

Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets.

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2300018660]