

Nafuflex GIP

Silicate primer for concrete, masonry and plaster surfaces



PRODUCT PROPERTIES

- Cost-effective concentrate
- Firms substrates
- Water permeable to vapour
- Solvent-free

AREAS OF APPLICATION

- Firming of powdery and dusty substrates
- Primer for the Nafuflex-sealing system
- Sealing of finely-porous, moist concrete and plaster surfaces and pre-cast elements

APPLICATION ADVICE

Substrate Preparation: Nafuflex GIP is used as a primer for the Nafuflex-sealing system; either undiluted or mixed with water at a mixing ratio of 1:1, depending on the application and the substrate. Nafuflex GIP can be sprayed with standard spraying. Smaller areas can be treated with a brush.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Density	kg/dm ³	1.19	
Mixing ratio (with water)	l:l	1 : 1	
Application conditions	°C	≥ 5	air and substrate temperatures
Consumption (flat)	l/m ²		depending on the absorbency of the substrate
As a bond coat		0.2 - 0.3	diluted material
Colour		light blue	
Delivery form		10 l canister	
Storage			Can be stored in cool and dry conditions for at least 12 months in original unopened packs.

Safety instructions

Please note the safety information and advice given on the packaging labels and safety data sheets.

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2300018550]